

KANSAS WATER POLLUTION CONTROL
GENERAL MUNICIPAL SEPARATE STORM SEWER SYSTEM (MS4) PERMIT
AND AUTHORIZATION TO DISCHARGE UNDER
THE NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM

Pursuant to the provisions of Kansas Statutes Annotated 65-164 and 65-165, the Federal Water Pollution Control Act as amended, 33 U.S.C. 1251 et seq., the "Act",

Permittee:

Permittee's Address:

Drainage Basin:

is hereby authorized to discharge stormwater from the system as described herein in accordance with the limitations, conditions and requirements set forth in this general permit.

This general permit is effective _____, supersedes the previously issued general permit M-AANN-AANN and expires _____.

PERMIT AREA AND AUTHORIZED DISCHARGES

For permits with "SN" appearing in the last four digits of the Kansas Permit number:

"This permit covers all areas within the permittee's jurisdiction (the Permit Area). The Permit Area may change based upon areas incorporated into or removed from the permittee's jurisdictional area during the term of this permit."

For permits with "SU" appearing in the last four digits of the Kansas Permit number:

"This permit covers all areas within the permittee's jurisdiction which are also located in the urbanized area as defined by the 2010 U.S. Census (the Permit Area). The Permit Area may change based upon areas incorporated into or removed from the permittee's jurisdictional area during the term of this permit."

For all permits:

This permit authorizes all existing or new stormwater point source discharges which discharge to waters of the state from the Municipal Separate Storm Sewer System (MS4) located within the Permit Area. New stormwater discharges are those which are created during the term of this permit.

Secretary, Kansas Department of Health and Environment

Date

PART I. STORMWATER MANAGEMENT PROGRAM (SMP) DOCUMENT REQUIREMENTS

- A. Current Stormwater Management Plan - The permittee shall continue to implement, and enforce the current Stormwater Management Program (SMP) until an updated SMP is implemented.
- B. Updated Stormwater Management Plan - The current SMP document shall be updated to include the additional requirements in this permit. The updated SMP shall be designed to:
1. reduce the discharge of pollutants from the MS4 to the Maximum Extent Practicable (MEP),
 2. continue to implement the six minimum control measures,
 3. satisfy the requirements of this permit, the Clean Water Act and Kansas surface water quality statutes and regulations.
- Implementation of Best Management Practices (BMPs) consistent with the provisions of the SMP and this permit constitutes compliance with the standard of reducing pollutants to the Maximum Extent Practicable.
- C. Six Minimum Controls - The Permittee shall continue to review, update and implement BMPs with measureable goals for each of the six minimum control measures. The six minimum control measures are:
1. Public Education and Outreach
 2. Public Involvement and Participation
 3. Illicit Discharge Detection and Elimination
 4. Construction Site Stormwater Runoff Control
 5. Post-Construction Stormwater Management in New Development and Redevelopment Projects
 6. Pollution Prevention/Good Housekeeping for Municipal Operations
- D. Total Maximum Daily Load (TMDL) Regulated Pollutants - The Permittee shall continue to review, update, implement and develop, when necessary, BMPs which will reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants as listed in PART II. The updated SMP shall provide:
1. Selection of Best Management Practices (BMPs)

The permittee shall provide an updated SMP document which discusses the BMPs that will be implemented to reduce the discharge of TMDL regulated pollutants. The SMP shall identify:
 - a. which BMPs will be implemented. Implemented BMPs for specific pollutants may be selected from the suite of BMPs assessed and presented in the International Stormwater BMP Database (<http://www.bmpdatabase.org>),
 - b. the location of the BMPs, if structural,
 - c. the design factors associated with the BMPs, if structural,
 - d. the reported effectiveness of the chosen BMPs,
 - e. a schedule for constructing and/or implementing the BMPs,
 - f. an inspection/maintenance plan and schedule for each BMP, as appropriate,
 - g. a plan and schedule to monitor the effectiveness of the BMPs.
 2. Establishing measurable goals to assess the effectiveness of the TMDL BMPs
 - a. Measurable goals shall be based upon instream/inlake sampling of the main stream(s)/lake(s) existing in, or entering and leaving the Permit Area during storm events.

- b. Measurable goals shall be expressed in quantifiable values to:
 - 1) reduce the average concentration of pollutants added by the stormwater discharge,
 - 2) reduce the total mass of pollutants discharged,
 - 3) a combination of the above methods.

3. Maps illustrating:

- a. the Permit Area,
- b. boundaries of the contributing drainage basins and primary sub-basins, within and outside the Permit Area,
- c. the locations of the BMPs, if structural,
- d. the stormwater BMP effluent, lake and stream monitoring locations, as appropriate
- e. storm sewer collection system which includes the outfalls within the Permit Area where the MS4 drains to TMDL listed impaired streams or lakes.

4. Stormwater Offsite Pollution Reduction Program - As appropriate, when waters of the state are affected by TMDL regulated pollutants from both the Permit Area and surrounding non-jurisdictional lands, the permittee should incorporate plans for an offsite pollution reduction program. The stormwater offsite pollution reduction program should be developed with watershed interests lying outside the Permit Area for the joint purpose of reducing pollutant loads generated from urban and non-urban lands within the shared watershed.

E. The parties responsible for compliance with the SMP document.

F. Monitoring Requirements - See Part III.

G. Reporting Requirements - See Part V.

H. Modifications to BMPs and the Stormwater Management Program document

For minor BMP modifications: Within 60 days of a determination by the permittee or by written notification from KDHE, the permittee shall modify the BMP if modifications are needed to achieve the goals of the program.

For major BMP modifications/replacement: Within 60 days of a determination by the permittee or by written notification from KDHE, the permittee shall provide a plan and schedule for the upgrade/replacement of the BMP. The plan and schedule are subject to KDHE approval.

The SMP shall be evaluated annually and modifications, if necessary, submitted with the annual report due to KDHE by February 28 of each year.

PART II. TOTAL MAXIMUM DAILY LOAD (TMDL) BEST MANAGEMENT PRACTICES

The permittee shall implement Best Management Practices (BMPs) to reduce to the Maximum Extent Practicable the discharge of the TMDL regulated pollutants to the impaired watershed stream and/or lake as listed below:

T M D L T A B L E

TMDL Regulated Pollutant	Impaired Watershed Stream or Lake

PART III. MONITORING REQUIREMENTS, FREQUENCY AND PARAMETERS

Monitoring Requirements

Storm Event Monitoring: The permittee shall implement a wet weather monitoring program for the Municipal Separate Storm Sewer System to assess the effectiveness of BMP control measures implemented under the SMP. Sampling and analysis will include, at a minimum, instream monitoring of the main stream(s) entering and leaving the jurisdictional Permit Area for the pollutants identified by the governing TMDLs. For impaired lakes within the Permit Area, monitoring of conditions within those lakes will be done after rainfall has ceased and runoff into those lakes has curtailed. Additionally, monitoring of stormwater flowing within the Permit Area, discharges from MS4 outfalls, or discharges from areas with BMPs may be done at the permittee's discretion to assist in management and evaluation of the BMPs and the SMP.

Monitoring Frequency and Periods

- A. Four storm events per year per monitoring site (Storm event shall mean a 24-hr rain or snow melt event of greater than or equal to 0.50 inches.),
- B. Monitoring shall be conducted in the spring (between March 1 and June 30) and summer (between July 1 and October 31) for the parameters as appropriate based upon the impairment.

Parameters

<u>TMDL Impairment</u>	<u>Parameter to be Monitored</u>	<u>MRL*</u>	<u>Sample Type</u>
Nutrients	Total Phosphorus as P (mg/l)	0.05	Grab
Nutrients	Nitrate+Nitrite as N (mg/l)	0.10	Grab
Nutrients	Total Kjeldahl Nitrogen (mg/l)	0.10	Grab
Nutrients	Total Nitrogen (mg/l)		Calculate**
Nutrients	Dissolved Oxygen (mg/l)	0.10	Grab
Sediment	Total Suspended Solids (mg/l)	10	Grab
Sediment	Turbidity (NTU)		Grab
Sediment (Lake)	Secchi Disk, (Ft)		Visual
Bacteria	E. coli (Col/100 ml or MPN)	10	Grab
Others	As provided by KDHE		As provided by KDHE

* Minimum Reportable Limit

** Total Nitrogen = Total Kjeldahl Nitrogen + Nitrate+Nitrite.

In addition, for streams at the time of sampling:

Rainfall, inches (last 24 hours)	Gauge Reading
Stream Flow, CFS or Stream Depth from a standard - Feet	Estimate/Reading
Stream Level (rising, falling, steady)	Describe
Stream Velocity (rapid, normal, still(backwater))	Describe

Grab samples for instream monitoring are to be obtained within 4 hours of rising stages on streams entering and leaving the Permit Area. Monitoring of a storm event for the purpose of complying with the stormwater monitoring and reporting requirements of this permit is not allowed if there is not at least 24 hours between this sampling storm event and the end of the previous rainfall event.

PART IV. PERMIT COMPLIANCE ACTIVITIES AND DEADLINES

- A. Year 1: Complete inventory and maps of the outfalls, streams, and lakes in the targeted areas, select drainage basins and sub-basins as candidates for BMPs, select and initiate design of appropriate BMPS.
- B. Year 2: Complete design of selected BMPs, initiate installation of BMPs, and initiate monitoring of storm events at selected sites.
- C. Years 3 & 4: Continue BMP installation and stream/lake/BMP outfall monitoring as appropriate.
- D. Year 5: Complete BMP installation, continue stream/lake/BMP outfall monitoring, report on effectiveness of BMPs to achieve the measureable goals and summarize water quality data from selected monitoring sites.
- E. A copy of the initial updated/implemented SMP document developed pursuant to this permit's requirements shall be submitted to KDHE for review by February 28, 2014. Subsequent annual reports shall be submitted to KDHE by February 28 of each year for the proceeding calendar year.

PART V. REPORTING

The permittee shall submit a calendar year annual report to KDHE by February 28 of each year. The report shall cover the activities during the previous calendar year and must include:

- A. the status of compliance with permit conditions, an assessment of the appropriateness of the Best Management Practices, progress towards achieving the statutory goal of reducing the discharge of pollutants to the maximum extent practicable (MEP), and the measurable goals (with an indication of the progress toward meeting the goals) for each of the six minimum control measures and TMDLs as listed in the Stormwater Management Program document;
- B. results of information collected and analyzed, if any, during the annual reporting period, including stormwater monitoring data used to assess the success of the program at reducing the TMDL regulated pollutants;
- C. a summary of the stormwater activities that were scheduled to be undertaken during the previous calendar year and the status of these activities;
- D. a summary of the stormwater activities which are scheduled to be undertaken during the next reporting cycle (including an implementation schedule);

- E. a map showing changes in the permittee's jurisdictional Permit Area;
- F. description of significant changes in any of the six minimum control measures;
- G. updated ordinances or resolutions associated with the SMP or the six minimum control measures shall be provided with the annual reports.
- H. a list of other parties, if any, which will be responsible for implementing any of the program areas of the Stormwater Management Program.

STANDARD CONDITIONS FOR
KANSAS WATER POLLUTION CONTROL AND
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM MS4 GENERAL PERMITS

1. Representative Sampling and Monitoring Report Submittals:

- A. Samples and measurements taken as required herein shall be representative of the quality of the monitored water. Test results shall be recorded for the day the samples were taken. All samples shall normally be taken at the locations designated by the permittee in the Stormwater Management Plan according to the requirements of this permit. In the event samples must be obtained from a location different than that designated in the Stormwater Management Plan the annual report shall indicate the change of location and provide the justification therefore.
- B. Monitoring results shall be recorded and reported on forms acceptable to the Division and provided in the annual report. Signed and certified copies of the annual report prepared in accordance with KAR 28-16-59, and all other reports required herein, shall be sent by U.S. mail to:

Kansas Department of Health & Environment
Bureau of Water-Municipal Programs Section
1000 SW Jackson Street, Suite 420
Topeka, KS 66612-1367

2. Definitions:

- A. A "grab sample" is an individual sample collected in less than 15 minutes. A "composite sample" is a combination of individual samples in which the volume of each individual sample is proportional to the flow, or the sample frequency is proportioned to the flow rate over the sample period, or the sample frequency is proportional to time.
- B. The terms "Director", "Division", and "Department" refer to the Director, Division of Environment, Kansas Department of Health and Environment, respectively.
- C. "Severe property damage" means substantial physical damage to property, damage to the treatment/control facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a diversion.

3. Duty to Mitigate: The permittee shall take all reasonable steps to minimize or prevent any damage to the environment or hazard to human health from any discharge in violation of this permit.

4. Test Procedures: All analyses required by this permit shall conform to the requirements of 40 CFR Part 136, unless otherwise specified, and shall be conducted in a laboratory accredited by the Department. For each measurement or sample, the permittee shall record the exact place, date, and time of measuring/sampling; the date and time of the analyses, the analytical techniques or methods used, minimum detection or reportable level, and the individual(s) who performed the measuring/sampling and analysis and, the results. If the permittee monitors any pollutant at the location(s) designated herein more frequently than required by this permit, using approved procedures, the results shall be included in the Monitoring Report form required in 1.B. above. Such increased frequencies shall also be indicated.

1. Change in Discharge: All stormwater discharges shall be in compliance with the conditions of the permit. Modification or expansion of the storm sewer system is allowed. All new storm sewer segments and outfalls constructed after the effective date of the permit, which are located within the permit area, are authorized under the permit and must comply with the permit conditions.

2. Proper Operations and Maintenance: The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the requirements of this permit and Kansas and Federal law.

7. **Incident Reporting:** The permittee shall report any unanticipated significant incidents which would be expected to result in non-compliance with the permit requirements within 24 hours from the time the permittee became aware of the incident. A written submission shall be provided within 5 days of the time the permittee became aware of the incident. The written submission shall contain a description of the noncompliance and its cause, the period of noncompliance, including exact dates and times; and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and steps taken or planned to reduce, eliminate, and prevent recurrence of the noncompliance.

For an anticipated incident or any planned changes or activities in the permitted control/treatment facility that may result in noncompliance with the permit requirements, the permittee shall submit written notice, if possible, at least ten days before the date of the event.

8. **Removed Substances:** Solids, sludges, debris, or other pollutants removed in the course of control/treatment of stormwater shall be utilized or disposed of in a manner acceptable to the Division.
9. **Right of Entry:** The permittee shall allow authorized representatives of the Division of Environment or the Environmental Protection Agency upon the presentation of credentials, to enter upon the permittee's premises where a stormwater discharge or source is located, or in which are located any records required by this permit, and at reasonable times, to have access to and copy any records required by this permit, to inspect any facilities, monitoring equipment or monitoring method required in this permit, and to sample any stormwater discharges from or influents into the stormwater control/treatment facilities.
10. **Transfer of Ownership:** The permittee shall notify the succeeding owner or controlling person of the existence of this permit by certified letter, a copy of which shall be forwarded to the Division. The succeeding owner shall secure a new permit. This permit is not transferable to any person except after notice and approval by the Director. The Director may require modification or revocation and reissuance of the permit to change the name of the permittee and incorporate such other requirements as may be necessary.
11. **Records Retention:** Unless otherwise specified, all records and information resulting from the monitoring activities required by this permit, including all records of analyses and calibration and maintenance of instruments and recordings from continuous monitoring instruments, shall be retained for a minimum of 3 years, or longer if requested by the Division.
12. **Availability of Records:** Except for data determined to be confidential under 33 USC Section 1318, all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. Treated and raw stormwater data shall not be considered confidential. Knowingly making any false statement on any such report or tampering with equipment to falsify data may result in the imposition of criminal penalties as provided for in 33 USC Section 1319 and KSA 65-170c.
13. **Permit Modifications and Terminations:** As provided by KAR 28-16-62, after notice and opportunity for a hearing, this permit may be modified, suspended or revoked or terminated in whole or in part during its term for cause as provided, but not limited to those set forth in KAR 28-16-62 and KAR 28-16-28b through g. The permittee shall furnish to the Director, within a reasonable amount of time, any information which the Director may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The permittee shall also furnish upon request, copies of all records required to be kept by this permit. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.
14. **Administrative, Civil and Criminal Liability:** The permittee shall comply with all requirements of this permit. Nothing in this permit shall be construed to relieve the permittee from administrative, civil or criminal penalties for noncompliance as provided for in KSA 65-161 et seq., and 33 USC Section 1319.
15. **Oil and Hazardous Substance Liability:** Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities or penalties to which the permittee is or may be subject to under 33 USC Section 1321 or KSA 65-164 et seq. A permittee shall promptly notify the Division by telephone upon discovering crude oil or any petroleum derivative in its storm sewer system or stormwater control/treatment facilities.
16. **Industrial Users:** A municipal permittee shall require any industrial user of the stormwater system to comply with 33 USC Section 1308.

17. **Property Rights:** The issuance of this permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to private property or any invasion of personal rights nor any infringements of or violation of federal, state or local laws or regulations.
18. **Severability:** The provisions of this permit are severable. If any provision of this permit or any circumstance is held invalid, the application of such provision to other circumstances and the remainder of the permit shall not be affected thereby.
19. **Removal from Service:** The permittee shall inform the Division at least three months before any control/treatment unit, or any other part of the control/treatment facility permitted by this permit is to be removed from service and shall make arrangements acceptable to the Division to decommission the facility or part of the facility being removed from service such that the public health and waters of the state are protected.
20. **Duty to Reapply:** A permit holder wishing to continue any activity regulated by this permit after the expiration date, must apply for a new permit at least 180 days prior to expiration of the permit.