

**Appendix M**  
**BER ARARs Policy and RSK Manual**

**BUREAU OF ENVIRONMENTAL REMEDIATION/REMEDIAL SECTION  
POLICY  
POTENTIAL APPLICABLE OR RELEVANT AND  
APPROPRIATE REQUIREMENTS (ARARs)**

**BER Policy #BER-RS-015**

**Date:** May 1995, Revised December 2001

**Pages:** 10

The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) of 1980 as amended by the Superfund Amendments and Reauthorization Act of 1986, stipulates that the cleanup standards or controls for hazardous substances, pollutants or contaminants be at least in accordance with any applicable or relevant and appropriate requirement (ARAR) designated under state or federal law (CERCLA §121(d)). Applicable requirements are those cleanup standards or controls that are promulgated under state or federal law that specifically address a hazardous substance, pollutant or contaminant, action, location or other situation at a site. Relevant and appropriate requirements are those cleanup standards or controls that do not specifically or fully address a hazardous substance, pollutant or contaminant, action, location or other situation at a site, but address similar situations.

There are three general categories of ARARs: 1) chemical-specific; 2) location-specific; and 3) action-specific. Chemical-specific ARARs are those that pertain to handling or control of certain chemicals based on health concerns or risks. Location-specific ARARs are those that control activities based on the location such as flood plains, wetlands, historic sites, or sensitive ecosystems. Action-specific ARARs are those that govern discrete actions that may include the use of certain technologies for remedial actions or use of certain types of equipment. At its discretion, KDHE may also identify policies or guidelines that are to be considered (TBC) standards for a site. TBC standards have not been promulgated but are used in conjunction with ARARs to achieve acceptable risk levels at a site.

ARARs must be identified during the Remedial Investigation/Feasibility Study (RI/FS) stage or other appropriate or comparable stage of the remedy process. ARARs should also be identified during Removal Actions where practicable, given consideration to the critical nature of the situation. A list of some federal and state laws and regulations is provided below to aid in identifying ARARs for Remedial and Removal Actions for sites in Kansas. The list of federal and state laws identified may not be comprehensive. The responsible party and KDHE project manager should work together to identify all ARARs and other standards that pertain to Remedial Actions for a site.

**Abbreviations:**

ARAR - Applicable or Relevant and Appropriate Requirements  
CFR - Code of Federal Regulations  
K.A.R - Kansas Administrative Regulation  
U.S.C. - United States Code

<b>Potentially Applicable Relevant and Appropriate Requirements (Federal)</b>	<b>Description</b>	<b>Comment</b>
<p><b>Archaeological and Historic Preservation Act of 1974</b></p> <p>16 U.S.C. § 469 et seq.</p>	<p>Provides for the preservation of historical or archaeological data which might be destroyed or lost as the result of 1) flooding, building of access roads, relocation of railroads and highways, and other alterations of terrain caused by the construction of a dam by government or persons, or 2) alteration of terrain caused by Federal construction projects or federally licensed activity or program.</p>	<p>Will be applicable if construction projects or alteration of terrain at a site have the potential to destroy historical or archaeological materials.</p>
<p><b>Clean Air Act (CAA)</b></p> <p>42 U.S.C. § 7401 et seq. as amended in 1977 and 1990</p> <p>Standards of Performance for New Stationary Sources (40 CFR 60)</p> <p>National Emission Standards for Hazardous Air Pollutants (40 CFR 61)</p> <p>National Emission Standards for Hazardous Air Pollutants for Source Categories (40 CFR 63)</p>	<p>Regulates air emissions from area, stationary, and mobile sources. Authorizes EPA to establish National Ambient Air Quality Standards.</p> <p>Identifies standards of performance for new stationary sources of air emissions. Provides emission guidelines and compliance times.</p> <p>Identifies emission standards for specific hazardous air pollutants.</p> <p>Identifies emission standards for hazardous air pollutants that originate from specific categories of sources.</p>	<p>May be applicable if remedial actions result in emissions of contaminants to the air.</p> <p>Will be applicable for new stationary sources of air emissions.</p> <p>Will be applicable if the identified hazardous air pollutants are emitted from a site.</p> <p>Will be applicable if the identified hazardous air pollutants are emitted from a specific source category that has been identified.</p>

<b>Potentially Applicable Relevant and Appropriate Requirements (Federal)</b>	<b>Description</b>	<b>Comment</b>
<p><b>Clean Water Act (CWA) of 1977</b> 33 U.S.C. § 1251 et seq. as amended in 1987</p> <p>National Pollutant Discharge Elimination System (NPDES) (40 CFR 122)</p> <p>Storm Water Discharge Requirements NPDES (40 CFR 122.26)</p> <p>Federal Water Quality Standards (40 CFR 131)</p> <p>General Pre-treatment Regulations for Existing and New Sources of Pollution for Publicly Owned Treatment Works (POTW) (40 CFR 403)</p> <p>Wetlands Protection (40 CFR 22, 40 CFR 230 to 233, and 33 CFR 320 to 330)</p>	<p>Implements a system to impose effluent limitations on, or otherwise prevent, discharges of pollutants into any waters of the United States from any point source.</p> <p>Regulates discharges of pollutants from any point source into waters of the United States</p> <p>Provide requirements to obtain a permit to discharge to the storm water sewer system under the NPDES program</p> <p>Establishes methods and requirements for states in the development of ambient water quality criteria for the protection of aquatic organisms and/or the protection of human health.</p> <p>Provides effluent limitations and guidelines for existing sources, standards of performance for new sources, and pre-treatment standards for new and existing sources.</p> <p>Allows for permitting of discharge of dredged or fill material to the waters of the United States if no practicable alternatives exist that are less damaging to the aquatic environment. Applicants must demonstrate that the impact to wetlands is minimized.</p>	<p>Will be applicable if discharges to streams, rivers, or lakes occur from a site.</p> <p>Will be applicable if water from the site will be discharged onto land or into streams, rivers or lakes.</p> <p>Will be applicable if the site has storm water that comes in contact with construction or industrial activity or if the selected remedy involves discharge of treated water to surface waters.</p> <p>May be indirectly applicable to surface water remediation and is directly applicable to surface water discharges.</p> <p>Will be applicable if wastewater from a site is discharged to a POTW.</p> <p>Will be applicable if designated wetlands are impacted by a remedy.</p>
<p><b>Comprehensive Environmental Response, Compensation and Liability Act (CERCLA) of 1980</b> 42 U.S.C. § 9601 et seq. as amended by the Superfund Amendments and Reauthorization Act (SARA) of 1986</p> <p>National Oil and Hazardous Substances Pollution Contingency Plan (NCP) (40 CFR 300)</p>	<p>Enacted to provide Federal authority to respond directly to releases or threatened releases of hazardous substances that may endanger public health and the environment. Established a trust fund (i.e., Superfund) to provide for cleanup when no responsible party is identified. Provides for liability of persons responsible for releases of hazardous substances. Established prohibitions and requirements concerning closed and abandoned hazardous waste sites.</p> <p>Federal government's blueprint for responding to spills or releases of oil and hazardous substances.</p>	<p>Will be applicable if the site is on the EPA National Priorities List (NPL). May be applicable for any site where a release of hazardous substances has occurred.</p>

<b>Potentially Applicable Relevant and Appropriate Requirements (Federal)</b>	<b>Description</b>	<b>Comment</b>
<b>Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986</b>  42 U.S.C. § 11001 et seq.	Designated to help local communities protect public health, safety and the environment from chemical hazards. Enables states and communities to prepare to respond to unplanned releases of hazardous substances. Requires facilities at which hazardous substances are present to report the presence of these materials to emergency responders. Requires companies to report the release of hazardous substances.	Will be applicable if hazardous chemicals are stored or used at a facility.
<b>Endangered Species Act of 1973</b>  7 U.S.C. § 136; 16 U.S.C. § 460 et seq.	Provides a program for conservation of threatened and endangered plants and animals and the habitats in which they are found.	Will be applicable if threatened or endangered species, or their habitats are present at or near a site.
<b>Explosives</b>  18 U.S.C. § 847	Regulates commerce in explosives. Requires licensing and permitting, record keeping and reporting for purchase and use of explosives. Provides standards for storage of explosive materials.	Will be applicable if explosives are purchased, stored or used at a site.
<b>Federal Hazardous Materials Transportation Law</b>  49 U.S.C. § 5101 et seq.	Regulates the transportation of hazardous wastes and hazardous substances by aircraft, railcars, vessels, and motor vehicles. Requires employers to train, test and maintain training records for all hazmat employees.	Will be applicable if hazardous materials are transported to or from a site.
<b>Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) of 1972</b>  7 U.S.C. § 136 et seq.	Provides Federal control of pesticide distribution, sale and use. Allows EPA to study the consequences of pesticide use. Requires users of pesticides to take exams for certification as applicators of pesticides. Pesticide users must register purchases of these materials.	May be applicable if pesticides were distributed, sold or used at a site.
<b>Fish and Wildlife Conservation Act</b>  16 U.S.C. § 2901 to 2911	Action to conserve fish and wildlife, particularly those species which are indigenous to the state.	Will be applicable if significant populations are present at a site or they are affected by site activities.
<b>Fish and Wildlife Coordination Act</b>  16 U.S.C. § 661-667e	The Act allows the Departments of Agriculture and Commerce to assist Federal and State agencies to study the effects of domestic sewage, trade wastes, and other polluting substances on wildlife.	Will be applicable if significant populations are present at a site or they are affected by site activities.
<b>Flood Control Act of 1944</b>  16 U.S.C. § 460	Provides the public with knowledge of flood hazards and promotes prudent use and management of flood plains.	Will be applicable if a site is located on a designated flood plain.
<b>National Historic Preservation Act of 1966</b>  16 U.S.C. § 470 et seq.	Establishes a national registry of historic sites. Provides for preservation of historic or prehistoric resources.	Will be applicable if a site is listed on historic registry and if activities requiring permitting are initiated at a site.

<b>Potentially Applicable Relevant and Appropriate Requirements (Federal)</b>	<b>Description</b>	<b>Comment</b>
<p><b>Occupational Safety and Health Act (OSHA) of 1970</b></p> <p>29 U.S.C. § 651 et seq.</p> <p>Occupational Safety and Health Standards (29 CFR 1910)</p> <p>Safety and Health Regulations for Construction (29 CFR 1926)</p>	<p>Enacted to ensure worker and workplace safety. Employers are required to provide workers a place of employment that is free from recognized hazards to safety and health.</p> <p>Provides standards for workers and the workplace including: working surfaces; means of egress; ventilation; noise; hazardous materials; personal protective equipment; sanitation; medical services and first aid; fire protection, detection, and suppression; materials handling and storage; machinery and machinery guards; power tools; and welding and electrical equipment. Also requires training for workers.</p> <p>Provides standards for construction activities including: work practices; safety equipment; scaffolding and ladders; fall protection; heavy equipment; excavations; concrete and masonry construction; steel erection; tunnels and shafts; demolition; use of explosives; power transmission and distribution; and overhead protection.</p>	<p>Applies to workers and workplaces.</p> <p>Will be applicable to workers and workplaces including hazardous waste sites.</p> <p>Will be applicable to workers and workplaces where construction activities take place.</p>

<b>Potentially Applicable Relevant and Appropriate Requirements (Federal)</b>	<b>Description</b>	<b>Comment</b>
<p><b>Resource Conservation and Recovery Act (RCRA) of 1976</b></p> <p>42 U.S.C. § 6901 et seq. as amended by the Hazardous and Solid Waste Amendments of 1984 (HSWA) and 1986, the Federal Facilities Compliance Act of 1992, and the Land Disposal Program Flexibility Act of 1996.</p> <p>Solid Waste Disposal Facility Criteria (40 CFR 257 - 258)</p> <p>Standards for Identification and Listing of Hazardous Waste (40 CFR 261)</p> <p>Standards Applicable to Generators of Hazardous Waste (40 CFR 262)</p> <p>Standards Applicable to Transporters of Hazardous Waste (40 CFR 263)</p> <p>Standards for Owners and Operators of Hazardous Waste Treatment, Storage, and Disposal Facilities (40 CFR 264)</p> <p>Manifesting, Record Keeping, and Reporting Requirements (40 CFR 264.70 to 264.77)</p> <p>Releases from Solid Waste Management Units (40 CFR 264.90 to 264.101)</p> <p>Closure and Post Closure Requirements (40 CFR 264.110 to 264.120)</p>	<p>Enacted to provide control of hazardous waste by imposing management requirements on generators and transporters of hazardous waste and upon owners and operators of treatment, storage and disposal (TSD) facilities. Also set forth a framework for management of non-hazardous waste. Focuses only on active or future facilities. HSWA requires phasing out land disposal of hazardous waste.</p> <p>Regulations apply to owners and operators of facilities that treat, store or dispose of solid wastes</p> <p>Provides criteria for identification of hazardous and solid wastes.</p> <p>Regulates the manifesting, pre-transport requirements, and record keeping and reporting for hazardous waste generators.</p> <p>Establishes standards which apply to persons transporting hazardous waste within the United States if the transportation requires a manifest under RCRA.</p> <p>Regulations apply to owners and operators of facilities that treat, store, or dispose of hazardous waste through the use of surface impoundments, waste piles, incinerators, land treatment units, and landfills.</p> <p>These standards apply to owners and operators of all facilities which treat, store or dispose of hazardous wastes</p> <p>Regulations apply to owners or operators of hazardous waste treatment, storage or disposal facilities.</p> <p>Facility owner or operator must close a hazardous waste facility in a way that minimizes the need for further maintenance and maximizes the protection of human health and the environment.</p>	<p>Applies to active hazardous and solid wastes including facilities that treat, store and dispose of these materials as well as generators and transporters of hazardous wastes.</p> <p>Will be applicable if site activities are analogous to solid waste facility activities.</p> <p>Will be applicable for identifying hazardous wastes.</p> <p>Will be applicable if hazardous waste is generated at a site.</p> <p>Will be applicable if hazardous waste is disposed off site.</p> <p>Will be applicable if site activities are analogous to hazardous waste facility activities.</p> <p>Will be applicable if site activities are analogous to hazardous waste facility activities.</p> <p>Will be applicable if solid waste is stored at a site.</p> <p>Will be applicable upon the closure and post closure of a hazardous waste facility.</p>

Potentially Applicable Relevant and Appropriate Requirements (Federal)	Description	Comment
<p><b>Resource Conservation and Recovery Act (RCRA)</b></p> <p>Interim Status Standards for Owners and Operators of Hazardous Waste Treatment, Storage and Disposal Facilities (40 CFR 265)</p> <p>Land Disposal Restrictions (40 CFR 268)</p> <p>Technical Standards and Corrective Action Requirements for Owners and Operators of Underground Storage Tanks (40 CFR 280)</p>	<p>Regulations apply to owners and operators of facilities that treat, store, or dispose of hazardous waste.</p> <p>Identifies hazardous wastes that are restricted from land disposal and defines those limited circumstances under which an otherwise prohibited waste may continue to be land disposed.</p> <p>Establishes regulations relating to underground storage tanks (UST) including: performance standards; spill control; corrosion protection; record keeping and reporting; release detection; environmental investigations of releases; corrective actions; and closure of UST systems.</p>	<p>Will be applicable if site activities are analogous to hazardous waste facility activities.</p> <p>Will be applicable depending on the type of waste generated at the site.</p> <p>Will be applicable if underground storage tanks are or were present at a site and if a petroleum release is present. Also provides for environmental assessment at closure of UST systems.</p>
<p><b>Safe Drinking Water Act (SDWA) of 1974</b></p> <p>42 U.S.C. § 300f et seq. as amended in 1986</p> <p>National Primary Drinking Water Regulations and Implementation (40 CFR 141 and 142)</p> <p>National Secondary Drinking Water Standards (40 CFR 143)</p> <p>Underground Injection Control Program (40 CFR 144 to 148)</p>	<p>Established to protect the quality of drinking water in the United States. Focuses on all waters actually or potentially designed for drinking use, whether from above ground or underground sources. The Act authorized EPA to establish safe standards of purity and required all owners or operators of public water supply systems to comply with primary (health-related) standards.</p> <p>Establishes maximum contaminant levels (MCLs) which are health risk based standards for public water systems.</p> <p>Establishes welfare-based secondary standards for public water systems.</p> <p>Assures that Underground Injection will not endanger drinking water sources. Provides regulations governing the use of underground injection wells including: identification of the classifications of injection wells; and the permitting, construction, operation, monitoring, testing, and reporting requirements. Also provides requirements for plugging of injection wells.</p>	<p>May be applicable, relevant or appropriate at sites where waters that are used or may potentially be used as drinking water supplies are impacted or threatened.</p> <p>Will be applicable at the distribution point (i.e., at the tap). Will be relevant and appropriate for groundwater cleanup at sites where potential drinking water sources (aquifers) are impacted.</p> <p>Will be applicable at the distribution point (i.e., at the tap).</p> <p>Will be applicable if underground injection of liquids or air is conducted as part of a site remedy.</p>
<p><b>Toxic Substances Control Act (TSCA) of 1976</b></p> <p>15 U.S.C. § 2601 et seq.</p>	<p>Enacted to give EPA the ability to track industrial chemicals currently produced or imported into the United States. EPA screens these chemicals and may require reporting or testing of those that pose an environmental or human-health hazard. EPA may ban the manufacture and import of those chemicals that pose an unreasonable risk.</p>	<p>Will be applicable if site activities involve handling of toxic substances such as polychlorinated biphenyls (PCBs) or remediation of these substances.</p>

<b>Potentially Applicable Relevant and Appropriate Requirements (Kansas)</b>	<b>Description</b>	<b>Comment</b>
<b>Ambient Air Quality Standards and Air Pollution Control</b> K.A.R. 28-19-1 to 28-19-801	Regulates air emissions from processing operations, indirect heating equipment, and incinerators. Establishes requirements for Attainment and Non-Attainment Areas. Establishes requirements for Stack Heights. Restricts open burning.	Will be applicable if a remedy results in the release of contaminants to the air.
<b>Asbestos Control</b> K.A.R. 28-50-1 to 28-50-14	Established the requirements for licensing of businesses and examination and certification of asbestos workers. Established requirement for notification of asbestos projects. Establishes work practices for asbestos projects. Establishes rules for disposal of asbestos containing materials.	Will be applicable if asbestos is handled or removed from a site or encapsulated.
<b>Agricultural Chemicals, Commercial Fertilizers, Anhydrous Ammonia, and Chemigation</b> K.A.R. 4-1-1 to 4-1-17, K.A.R. 4-4-1 to 4-4-984, K.A.R. 4-10-1 to 4-10-17, and K.A.R. 4-20-1 to 4-20-15	Requires labeling and registration of agricultural chemicals. Provides regulations for storage and secondary containment, transportation and record keeping for commercial fertilizers and anhydrous ammonia. Requires permitting and certification of operators of chemigation equipment.	Will be applicable if agricultural chemicals, commercial fertilizers or anhydrous ammonia are used at site. Will be applicable if chemicals or animal wastes are applied by chemigation.
<b>Construction, Operation, Monitoring and Abandonment of Salt Solution Mining Wells</b> K.A.R. 28-43-1 to 28-43-11	Regulates the construction, operation, monitoring, testing and abandonment of salt solution mining wells.	Will be applicable if salt solution mining wells are present.
<b>Emergency Planning and Right-to-Know</b> K.A.R. 28-65-1 to 28-65-4	Designated to help local communities protect public health, safety and the environment from chemical hazards. Enables communities to prepare to respond to unplanned releases of hazardous substances. Requires facilities at which hazardous substances are present to report the presence of these materials to emergency responders. Requires companies to report the release of hazardous substances.	Will be applicable if hazardous chemicals are stored or used at a site.
<b>Explosive Materials</b> K.A.R. 22-4-1 to 22-4-4	Requires all contractors to obtain explosive storage site permits before moving, storing or using any explosives or blasting agents at any job site within the state.	Will be applicable if explosives or blasting agents are used or stored at a site.
<b>Hazardous Waste Management Standards and Regulations</b> K.A.R. 28-31-1 to 28-31-16	Identifies the characteristics and listing of hazardous waste. Prohibits underground burial of hazardous waste except as granted by EPA or KDHE. Establishes restrictions on land disposal. Establishes standards for generators or transporters of hazardous waste. Establishes standards for hazardous waste storage, treatment and disposal facilities.	Will be applicable if hazardous wastes are present at a site.
<b>Hydrocarbon Storage Wells and Well Systems</b> K.A.R. 28-45-1 to 28-45-11	Establishes a system for permitting of hydrocarbon storage wells. Establishes requirements for construction, operation and monitoring, and plugging of hydrocarbon storage wells.	Will be applicable if hydrocarbon storage wells are present at a site.

<b>Potentially Applicable Relevant and Appropriate Requirements (Kansas)</b>	<b>Description</b>	<b>Comment</b>
<b>Kansas Board of Technical Professions</b> K.A.R. 66-6-1 through 66-14-12	Establishes the requirements for licensing of engineers, land surveyors, geologists and architects.	Will be applicable if the services of a geologist, engineer or land surveyor are required for site investigations or remediation.
<b>Kansas Drycleaner Environmental Response Act</b> K.A.R. 28-68-1 to 28-68-9	Enacted to provide funds to assist with assessment and corrective action of former and existing drycleaner facilities. Requires registration of drycleaning facilities and compliance with waste management measures.	May be applicable if a drycleaner operated onsite.
<b>Kansas Historic Preservation Act</b> K.A.R. 118-3-1 to 118-3-16	Provides for the protection and preservation of sites and buildings listed on state or federal historic registries.	Will be applicable if a site or building is listed on the state or federal historic registry and if activities requiring permitting are initiated at a site.
<b>Kansas Water Appropriations Act</b> K.A.R. 5-1-1 through 5-10-6 and K.A.R. 5-50-1 to 5-50-8	Establishes the requirements for obtaining, maintaining and transferring water appropriations.	Will be applicable if water appropriations are required for groundwater remediation.
<b>Mined Land Reclamation</b> K.A.R. 47-16-1 to 47-16-11	Allows for the reclamation of mined land and associated waters.	Will be applicable if mined land or associated waters are to be reclaimed.
<b>Non-Game, Threatened or Endangered Species</b> K.A.R. 115-15-1 to 115-15-4	Identifies Threatened and Endangered Species	Will be applicable if any of the identified species are present at a site.
<b>PCB Facility Construction Permit Standards and Regulations</b> K.A.R. 28-55-1 to 28-55-5	Establishes the requirement for permitting of facilities constructed for the treatment, storage or disposal of materials containing polychlorinated biphenyls (PCBs). Establishes standards for PCB facilities.	Will be applicable if treatment, storage or disposal of materials containing PCBs occurs.
<b>Pesticides</b> K.A.R. 4-13-1 to 4-13-65	Requires licensing of pesticide businesses and certification of persons that apply pesticides.	Will be applicable if pesticides are present at a site or application of pesticides occurs.
<b>Petroleum Products Storage Tanks</b> K.A.R. 28-44-1 to 28-44-29	Provides requirements for permitting of the installation and operation of underground storage tanks (USTs). Provides requirements for design and construction of storage tanks. Provides a system for licensing contractors who install and test USTs. Requires implementation of methods for detecting releases and reporting releases from USTs.	Will be applicable if petroleum storage tanks are or were present at a site.
<b>Radiation</b> K.A.R. 28-35-1 to 28-35-363	Regulations require registration of radiation producing devices and licensing of sources of radiation. Provides standards for protection against radiation. Provides requirements for industrial radiographic operations and wireline and subsurface tracer studies.	Will be applicable if radiation producing devices or sources of radiation are present at or are used at a site.

<b>Potentially Applicable Relevant and Appropriate Requirements (Kansas)</b>	<b>Description</b>	<b>Comment</b>
<b>Solid Waste Management</b> K.A.R. 28-29-1 to 28-29-121 and K.A.R. 28-29-2101 to 28-29-2113	Provides standards for management of solid wastes. Establishes administrative procedures. Establishes the requirement for development and submittal of Solid Waste Management Plans.	Will be applicable if solid waste is generated, stored or disposed at a site.
<b>Spill Reporting</b> K.A.R. 28-48-1 to 28-48-2	Requires reporting of unpermitted discharges or accidental spills. Requires that containment and immediate environmental response measures are implemented. Also provides for technical assistance for mercury-related spills.	Will be applicable if unpermitted discharges or accidental spills occur at a site.
<b>Underground Injection Control Regulations</b> K.A.R. 28-46-1 to 28-46-44	Provides regulations governing the use of underground injection wells including: identification of the classifications of injection wells; and the permitting, construction, operation, monitoring, testing, and reporting requirements. Also provides requirements for plugging of injection wells.	Will be applicable if the remedy involves the injection of fluids or air into the subsurface.
<b>Underground Storage, Disposal Wells and Surface Ponds</b> K.A.R. 28-13-1 to 28-13-9	Regulates the construction and use of underground storage reservoirs, disposal wells and surface ponds for the confinement, storage and disposal of industrial fluids including but not limited to brine. Also pertains to removal of material from surface ponds upon abandonment. Does not include regulations pertaining to oil field activities.	Will be applicable if underground reservoirs, disposal wells or surface ponds are used for storage or disposal of industrial fluids at a site. Will be applicable if use of a surface pond is discontinued.
<b>Voluntary Cleanup and Property Redevelopment Program</b> K.A.R. 28-71-1 to 28-71-12	Provides a mechanism for property owners, facility operators, prospective purchasers, and local governments to voluntarily address contaminated properties with technical and regulatory guidance from KDHE.	May be applicable if a site meets the criteria for acceptance into the Voluntary Cleanup Program
<b>Water Pollution Control</b> K.A.R. 28-16-1 to 28-16-154	Provides regulation of sewage discharge. Establishes pre-treatment standards for industry. Designates uses of rivers and streams. Establishes River Basin Quality Criteria and Surface Water Quality Criteria. Provides for the establishment of Critical Water Quality Management Areas.	Will be applicable if water is to be discharged to state waterways.
<b>Water Well Contractor's License; Water Well Construction and Abandonment</b> K.A.R. 28-30-1 to 28-30-10	Establishes the requirements for licensing of drillers. Regulates drilling activities including the construction of wells.	Will be applicable if drilling and/or well construction or abandonment is conducted at a site.

**RISK-BASED STANDARDS FOR KANSAS  
RSK MANUAL – 3<sup>rd</sup> VERSION**

**MARCH 1, 2003**



**KANSAS DEPARTMENT OF HEALTH AND ENVIRONMENT**

**DIVISION OF ENVIRONMENT**

**BUREAU OF ENVIRONMENTAL REMEDIATION**

## PREFACE:

*The Risk-Based Standards for Kansas (RSK) Manual was developed to assist Kansas Department of Health and Environment (KDHE)/Bureau of Environmental Remediation project managers to fairly and consistently address contaminated sites in the State of Kansas. The manual is only applicable to contaminated properties or sites that are participating in an appropriate state program. KDHE project managers will work with responsible parties to ensure appropriate application of this guidance.*

*This document is not intended to be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 values established in the RSK Manual without KDHE oversight may constitute misapplication of the RSK Manual and may result in risk management decisions not supported by KDHE.*

*This March 1, 2003 RSK Manual supercedes the September 4, 2001 version. The September 4, 2001 version is obsolete and should not be used for future decisions related to the characterization or remediation of contaminated properties/sites. This March 1, 2003 version of the RSK Manual contains several updates to the existing text, tables, and appendices. Modifications to the text are mostly of an editorial nature, although text has been added to Section 6.0 to better describe the use of soil saturation values for total petroleum hydrocarbons (TPH). Also, an entirely new discussion on nitrate and ammonia contamination is presented in Section 7.0. All modifications to the appendices have been printed in bold font.*

**BACKGROUND:** The Risk-based Standards for Kansas (RSK) Manual was originally developed in March of 1999 in collaboration with CH2M Hill, a private environmental contractor with expertise in risk assessments. Chemical-specific and media-specific risk-based cleanup goals were calculated using guidance and directives from the United States Environmental Protection Agency and various other technical resources. Prior to initial development of the RSK Manual, an Environmental Workgroup was established consisting of members of industry and the public to assist in determining appropriate risk-based cleanup levels. The risk-based cleanup levels determined by the Environmental Workgroup are incorporated into the RSK Manual. The RSK Manual assists the Kansas Department of Health and Environment (KDHE) to fairly and consistently address contaminated sites in the State of Kansas.

**LIMITATIONS ON USE:** The RSK Manual is only applicable to contaminated properties or sites that are participating in appropriate state cleanup programs. KDHE project managers will work with the public and industry to ensure appropriate application of this guidance. Tier 2 risk-based cleanup levels defined in the RSK Manual are applicable for a single contaminant, in a single medium, under standard and conservative default exposure assumptions. Tier 2 risk-based cleanup levels have several additional limitations. Specifically excluded from consideration are transfers of contaminants from soil to air, vapor intrusion of volatile contaminants from ground water to indoor air, cumulative risk from multiple contaminants or media, and risk to ecological receptors.

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. The RSK Manual is not intended for use by environmental consultants on contaminated sites in the State of Kansas that are not participating in a KDHE cleanup program.

## **Corrections made to manual since original printing.**

There are some mistakes in Appendix A of the RSK Manual regarding bis(2-ethylhexyl)phthalate. The value for the groundwater pathway should be .006 mg/L for both residential and non-residential scenarios. The soil-to-groundwater pathway value should be 18000 mg/kg for both scenarios. (The soil pathway numbers remain the same.) Please make the appropriate changes in your copies of the RSK Manual, and share these corrections with any affected facility contacts.

# RISK-BASED STANDARDS FOR KANSAS

## TABLE OF CONTENTS

1. INTRODUCTION . . . . .	1
2. PUBLIC USE OF RISK-BASED STANDARDS FOR KANSAS . . . . .	1
3. OVERVIEW . . . . .	3
4. SITE CHARACTERIZATION. . . . .	6
5. TIERED APPROACH . . . . .	7
5.1 TIER 1 . . . . .	7
5.2 TIER 2 . . . . .	8
5.2.1 EXPOSURE ASSESSMENT. . . . .	9
5.2.2 TOXICITY ASSESSMENT . . . . .	11
5.2.3 RISK CHARACTERIZATION . . . . .	11
5.2.3.1 GROUND WATER . . . . .	12
5.2.3.2 SOILS . . . . .	12
5.2.3.3 SOIL TO GROUND WATER PROTECTION . . . . .	13
5.3 TIER 3 . . . . .	14
6. TOTAL PETROLEUM HYDROCARBONS . . . . .	16
7. NITRATE AND AMMONIA . . . . .	18
8. TABLES, FORMULAS, AND EQUATIONS . . . . .	20
9. REFERENCES . . . . .	27
APPENDIX A. . . . .	TIER 2 RISK-BASED SUMMARY TABLE
APPENDIX B. . . . .	CONTAMINANT-SPECIFIC PARAMETERS
APPENDIX C. . . . .	CONTAMINANT TOXICITY DATA

# **RISK-BASED STANDARDS FOR KANSAS**

## **1.0 INTRODUCTION**

The Risk-Based Standards for Kansas (RSK) Manual is a guidance document which describes the process for establishing chemical-specific and site-specific cleanup goals for soil and ground water that are protective of human health and the environment. This document was created to establish a consistent and streamlined decision making process for addressing contaminated sites managed by the Kansas Department of Health and Environment (KDHE)/Bureau of Environmental Remediation (BER). The RSK Manual is meant to serve as a tool for evaluation of site conditions and the need for additional assessment or cleanup, when considered in conjunction with other site-specific conditions. The RSK Manual is a compilation of federal Safe Drinking Water Act Maximum Contaminant Levels (MCLs) for public drinking water supplies, risk-based cleanup goals for contaminants in soil and ground water for which federal standards have not been established, and supporting chemical, physical, and toxicological properties for the contaminants considered herein.

The procedures and methodologies contained in this document have been employed to be consistent with federal guidance and directives to assess potential human health risk posed by exposure to environmental contamination. Federal guidance and directives were established subsequent to the promulgation of the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) as amended by the Superfund Amendments and Reauthorization Act of 1986 (SARA). KDHE believes that proper employment of this manual will result in risk-based remediation that is consistent with federally promulgated standards, including the Safe Drinking Water Act, and is protective of human health as defined by the National Contingency Plan (NCP).

The document was developed through collaboration with CH2M Hill, a private environmental contractor with expertise in risk assessments. Chemical-specific and media-specific risk-based cleanup goals were calculated using guidance and directives from the United States Environmental Protection Agency (EPA) and other technical resources, which are referenced throughout this document and listed in Section 9, "REFERENCES." This document is the third edition of "Risk-Based Standards for Kansas," originally dated March 29, 1999, and supercedes all previous editions.

## **2.0 PUBLIC USE OF RSK**

The primary benefit of this document is the predetermination of acceptable cleanup goals without requiring the performance of costly and time-consuming baseline risk assessments and/or contaminant fate and transport models. Use of the RSK Manual offers many other benefits to Kansas industry, Kansas residents, and KDHE, including:

### BENEFITS OF THE RSK MANUAL:

- Streamlines the decision-making process;
- Promotes consistency;
- Ensures that remedial actions are protective of human health and the environment;
- Promotes flexibility by providing tabulated risk-based cleanup goals as well as the opportunity to develop site-specific cleanup goals;
- Considers land use; and,
- Provides the opportunity for the use of institutional controls and/or financial assurance to ensure that contamination remaining on site will not pose a future threat.

The document provides the public with a streamlined, cost-effective approach to determine whether some form of remedial action is warranted at a contaminated site. **Direct oversight and approval by KDHE in this determination is required.** The implementation or use of this document without the direct oversight and consent of KDHE does not constitute or convey the determination that no action is warranted at a contaminated site. Additional state, federal, and/or local laws or regulations may be applicable at certain sites. The user is responsible for compliance with these laws and regulations, and to obtain all applicable permits, approvals, authorizations, etc. The final selection of cleanup levels shall rest with the department. KDHE urges the public to consider the following when using the RSK document:

- Applicable or relevant and appropriate requirements may affect the selection or implementation of a cleanup approach for the site, i.e., zoning for land use designation, local public health laws and ordinances, ground water management districts, Resource Conservation and Recovery Act (RCRA), etc.;
- There may be additive effects posed by multiple contaminants and multiple pathways of exposure;
- Aesthetic or other criteria may drive the need for remediation independent of risk-based standards;
- KDHE's oversight and approval must be obtained to ensure that actions conducted at the site are consistent with and satisfy state laws, rules and regulations, guidance, and policies; and,
- The RSK Manual does not address the potential health risks associated with migration of contaminants from soil and ground water into indoor air.

### 3.0 OVERVIEW

The RSK Manual provides an overview of the rationale and process for determining soil and ground water cleanup levels for contaminated sites in Kansas. Detailed information on definitions, formulas, input parameters and the use of the three tiers are provided in the following sections. **This approach is not acceptable for all sites, so approval must be obtained from the state program responsible for regulating the site.**

- **TIER 1** – KDHE-approved methods to determine background concentrations;
- **TIER 2** – KDHE/BER Risk-Based Summary Table; or
- **TIER 3** – Site-specific technical analyses using KDHE-approved information, data, models, model input parameters or other methodologies to determine site-specific remedial actions or cleanup concentrations.

Human health risk is best described as the probability of suffering harm as a consequence of chronic, or long-term, exposure to contaminated media. Human health risk effects are generally classified into two separate categories. *Non-carcinogens* are contaminants that lack evidence of increasing the potential for developing cancer over a lifetime. *Carcinogens* are contaminants that have the potential to increase the potential for developing cancer over the lifetime of an exposed individual.

For *non-carcinogens* a threshold concentration is quantified for each contaminant based upon clinically-determined critical toxicological effects such as liver damage, kidney damage, central nervous system disorders, etc. The threshold concentration is referred to as the reference dose or RfD. The lower the RfD value for a contaminant, the more toxic it is relative to contaminants with higher RfDs. Exposure to a contaminant concentration below the RfD should not cause a critical toxicological effect; however, exposure to a contaminant concentration exceeding the RfD may cause a critical toxicological effect. Risk assessors calculate the ratio of a contaminant concentration to the RfD to determine the Hazard Index (HI). If the HI is less than or equal to 1, the contaminant concentration is considered acceptable. If the HI is greater than 1, the contaminant concentration is considered unacceptable and a response action may be required.

For *carcinogens*, the probability of increasing the potential for developing a cancer as a result of chronic exposure to contaminated media is quantified based upon clinical studies of exposed populations, including humans, where available, or test animals in the absence of documented human exposures. The contaminant-specific carcinogenic risk factor is referred to as the slope factor. Contrary to RfDs, the higher the slope factor value for a carcinogenic contaminant, the more toxic it is relative to carcinogenic contaminants with lower slope factors. Risk assessors quantify the probability of developing a cancer as a result of chronic exposure to carcinogenic contaminated media by multiplying the contaminant concentration by the contaminant slope factor. The resulting value is expressed in terms of one additional cancer incidence per population exposed; for example, one additional cancer incidence per ten thousand (1 in 10,000) exposed individuals, which may be expressed as  $1 \times 10^{-4}$ . EPA regulations state the  $1 \times 10^{-6}$  risk level shall be used as the point of departure for determining remediation goals for alternatives when applicable or relevant and appropriate requirements (ARARs) are not available or are not sufficiently protective because of the presence of multiple contaminants or multiple pathways of

exposure. Carcinogenic contaminants are also evaluated for their critical non-carcinogenic toxicological effect. The determining risk-based concentration is based upon the lower contaminant concentration of the carcinogenic risk or non-carcinogenic risk.

Soil cleanup goals are based upon one or more of the following considerations as defined in the various program policies and regulations. The primary goal of Bureau of Environmental Remediation programs is to insure that sites are remediated to the extent that the public are protected from unreasonable risks potentially caused by exposure to contaminated sites.

1. In the event naturally occurring<sup>1</sup> levels of an individual contaminant in soil exceed the cancer risk of  $1 \times 10^{-6}$  (1 in 1,000,000), or a hazard index value of 1.0, then the background level may be the cleanup level;
2. In the event that anthropogenic<sup>2</sup> levels of a contaminant in soil exceed the cancer risk of  $1 \times 10^{-6}$  (1 in 1,000,000), or a hazard index value of 1.0, then a  $1 \times 10^{-5}$  (1 in 100,000) cancer risk level, or a level corresponding to a hazard index value equal to 1.0 may be used as the cleanup levels;
3. A property-specific risk analysis performed in accordance with the department's scope of work shall be used to determine a property-specific cleanup level where the cancer risk exceeds  $1 \times 10^{-6}$  or the hazard index value exceeds 1.0. This site-specific cleanup level may not pose cumulative cancer risk of greater than  $1 \times 10^{-4}$  or a hazard index of greater than 1.0. Where carcinogenic contaminants drive the need for cleanup, the department will determine the appropriate level of cleanup within the  $1 \times 10^{-4}$  to  $1 \times 10^{-6}$  range based on site-specific considerations.
4. Property-specific cleanup levels shall be determined by the department for contaminants for which there is insufficient toxicological evidence to support a regulatory standard for risk-based cleanup levels or for nontoxic contaminants for which cleanup is required as a result of other undesirable characteristics of those contaminants. The levels shall be based on the following:
  - a) The ability of the impacted soil to support vegetation representative of non-impacted properties in the vicinity of the eligible property; and,
  - b) The potential of the contaminant to impact and degrade ground water, surface water, or both, through infiltration or runoff; and,
5. When there are multiple contaminants in the soil, the cleanup level of each contaminant shall not allow the cumulative risks posed by the contaminants to exceed a cancer risk of  $1 \times 10^{-4}$  (1 in 10,000), or a hazard index value of 1.0.

Ground water cleanup levels shall be based on the most beneficial use of the ground water considering present and proposed future uses. The most beneficial use of the ground water is for a potable water source, unless demonstrated otherwise by the voluntary party and approved by

---

<sup>1</sup> Naturally occurring chemicals or substances are defined as those chemicals or substances that are present in the environment at ambient concentrations unaffected by anthropogenic influences.

<sup>2</sup> Anthropogenic concentrations of chemicals or substances are defined as those chemicals or substances that are present in the environment as a result of human activity.

the department. The most beneficial use of ground water shall be determined by the department based upon available documentation, as well as documentation provided by the potentially responsible party. Ground water potentially or actually used as a potable water source shall require maximum protection in determining cleanup levels. The department shall approve cleanup levels that prevent additional degradation of the groundwater caused by contamination migration and that encourage remedial actions to restore contaminated groundwater to its most beneficial use. One or a combination of the following approaches to ground water cleanup shall be proposed and approved by the department:

1. In the event naturally occurring levels of an individual contaminant in ground water exceed the cancer risk of  $1 \times 10^{-6}$  (1 in 1,000,000), or a hazard index value of 1.0; then the background level may be the cleanup level;
2. In the event that anthropogenic levels of an individual contaminant in ground water exceed the cancer risk level of  $1 \times 10^{-6}$  (one 1 in 1,000,000), or a hazard index value of 1.0, then the maximum contaminant levels (MCLs) established by the federal government or a cancer risk level of  $1 \times 10^{-5}$  (1 in 100,000), or a level corresponding to a hazard index value equal to 1.0 shall be the cleanup level;
3. In the event that the chemical-specific maximum contaminant levels (MCLs) are not applicable or available, a property-specific risk analysis performed by the voluntary party in accordance with the department's scope of work shall be used to determine a property-specific cleanup level where the cancer risk exceeds  $1 \times 10^{-6}$  or the hazard index value exceeds 1.0. The site-specific cleanup level may not pose cumulative cancer risk of greater than  $1 \times 10^{-4}$  or a hazard index of greater than 1.0. Where carcinogenic contaminants drive the need for cleanup, the department will determine the appropriate level of cleanup within the  $1 \times 10^{-4}$  to  $1 \times 10^{-6}$  range based on site-specific considerations.
4. When the need for cleanup of a contaminant is predicated on characteristics of that contaminant other than toxicity, including the contribution of an undesirable taste or odor, or both, the site-specific cleanup level as determined by the department or secondary MCLs shall be used as cleanup levels for contaminants for which insufficient toxicological evidence has been gathered to support a regulatory standard. These levels shall be based on the aesthetic quality and usability of the ground water, surface water, or both, for the present and proposed future use;
5. When there are multiple contaminants in the ground water, the cleanup level of each contaminant shall be such that the cumulative risks posed by the contaminants shall not exceed a cancer risk level of  $1 \times 10^{-4}$  (1 in 10,000), or a hazard index value of 1.0; and,
6. Surface water cleanup levels shall meet the Kansas surface water quality standards, as defined in K.A.R. 28-16-28(b), et seq.

## 4.0 SITE CHARACTERIZATION

Elements of a basic site characterization generally include record searches to gather historical information. That information will be used to focus the collection of environmental data, which in turn will be used to identify source(s) of contamination, delineate the horizontal and vertical extent of contamination, and characterize the geology, including significant contaminant fate and transport mechanisms. The information and data collected during site characterization should be sufficient to develop a site-specific conceptual model and support the evaluation and selection of a remedial response, if appropriate. The conceptual model should identify all media impacted by contamination (soil, ground water, surface water, etc.), primary and secondary exposure pathways, and exposed or potentially exposed populations. Site characterization information and data combined with a site-specific conceptual model are used to develop site-specific remedial action objectives.

The KDHE/BER has developed various scopes of work which define the tasks necessary to satisfy the objectives of various stages of site characterization, data needs for potential Tier 3 technical analyses, and information necessary to evaluate potential remedial alternatives. These scopes of work and associated guidance are available from each of the individual programs. Essential elements of any environmental site characterization typically include:

- A review of historical records to identify, at a minimum, all chemicals used at the site, chemical storage and handling area, and chemical product and waste disposal methods;
- A visual inspection of the facility or property to identify observable evidence of chemical releases, such as stained soil, stressed vegetation, corroded flooring, etc.;
- The collection of samples for laboratory analysis from environmental media at locations that are likely to have been impacted by historical release(s) of the contaminants of concern;
- The characterization of the geology and hydrology of the property using intrusive technologies such as soil borings and monitoring wells and the performance of aquifer tests to evaluate the composition and stratigraphy of the subsurface and the intrinsic hydrologic properties of the aquifer(s) underlying the site;
- The evaluation of the background concentrations of the contaminants of concern in affected environmental media; and,
- The identification of threatened or impacted receptors including, but not limited to, residents, workers, private and public water supply wells, sensitive ecosystems, etc.

For site investigations where naturally occurring chemicals or substances are the contaminants of concern, background or ambient environmental quality will need to be characterized. Background environmental quality characterization is necessary in order to identify the contaminants of concern and their appropriate site-specific cleanup goals. Failure to adequately characterize background environmental quality conditions may result in unnecessary cleanups.

If pre-existing background environmental quality data is not available or not representative of the site, then the collection and analysis of background samples will be required to determine background environmental quality. A site-specific number of soil samples, approved by KDHE, collected from the same soil type in an area nearest the site unaffected by potential releases of naturally occurring contaminants of concern should be analyzed to characterize background soil concentrations. For ground water, data should be collected at a location(s) representing background ground water quality conditions. If naturally occurring chemicals, or substances, which are potential contaminants of concern, based upon their usage, treatment, storage, or disposal, are detected at concentrations in excess of background, remedial action may be warranted.

Information collected during the site characterization should be sufficient to classify current and likely future land uses for the site. Chemical-specific cleanup concentrations defined in this document are based upon land use and are separated into two general land use scenarios, residential<sup>3</sup> and non-residential<sup>4</sup>. In general terms, all sites should be considered residential unless information provided within the site characterization proves otherwise and is approved by KDHE. Documentation of non-residential classification may include information from local zoning and planning department offices documenting the current and likely future land uses as non-residential. Non-residential sites located directly adjacent to residential properties shall be considered residential unless there are controls limiting access to the site such as security fencing. Land use shall be confirmed by KDHE by performing a site inspection.

After completing site characterization, including adequately assessing background environmental quality, chemical-specific goals can be determined for the site. The tiered approach outlined in the next section prescribes the process for determining cleanup goals for each site.

## **5.0 TIERED APPROACH**

### **5.1 TIER 1**

Tier 1 cleanup levels are determined for contaminants of concern that are naturally present in the environment. This class of contaminants includes metals such as lead, arsenic, cadmium, and chromium, among others, and inorganic pollutants such as nitrate and chloride, among others. In addition, certain substances that are endemically enriched in various environments, such as industrial tracts or agricultural lands as a result of their widespread employment by humans, may be evaluated as a Tier 1 contaminant. For sites with naturally-occurring contaminants, the

---

<sup>3</sup> Residential land use means any property currently or proposed for use as a residence or dwelling, including a house, apartment, mobile home, nursing home or condominium; or public use area, including a school, educational center, day care center, playground, unrestricted outdoor recreational area or park.

<sup>4</sup> Non-residential land use means any property that does not exclusively meet the definition of residential land use.

background concentration shall be the cleanup level in soil and ground water where the background cancer risk level exceeds  $1 \times 10^{-6}$  (1 in 1,000,000), or a hazard index value exceeds 1.0, or other criteria defined in Section 3.0.

Accordingly, background concentrations must be determined for substances that are naturally-occurring that are contaminants of concern at the site. If pre-existing data are not available or are not representative of the site, then determining background concentrations is a necessary element of site characterization. A site-specific number of soil samples collected from the same soil type in an area not affected by contamination from the site and not impacted from other releases should be analyzed to characterize background soil concentrations. For ground water, data should be collected from an upgradient location to determine background concentrations of naturally occurring contaminants of concern.

Ultimately, it will be necessary to gain approval from the KDHE/BER project manager for sampling strategies meant to characterize background environmental quality. Background environmental quality data may be presented to the KDHE/BER project manager from pre-existing referenced sources of information or a sampling and statistical analysis plan for the determination of background concentrations may be submitted for approval prior to implementation. The method of drilling, constructing, developing, and sampling wells will have a significant impact on the ground water geochemistry, especially for metals.

KDHE considers the speciation of metals and other inorganics in soils when determining risk-based standards. The general definition of speciation is the molecular structure or oxidation states of a compound. For the Tier 1 and Tier 2 approach, KDHE considers the most toxic form of a naturally occurring compound to assure protectiveness. As an example, this approach is factored in the Tier 2 cleanup concentrations for chromium and cyanide listed in Appendix A. In the Tier 2 approach, KDHE assumes 100 percent of the chromium detected is hexavalent chromium ( $\text{Cr}^{+6}$ ), which is significantly more toxic compared to trivalent chromium ( $\text{Cr}^{+3}$ ). For cyanide, copper cyanide is the most toxic form of the cyanides, including free cyanide. For a majority of the naturally occurring compounds listed in the Tier 2 table a general risk-based value is provided for those compounds since there is insufficient toxicological data available to determine risk-based standards for the various forms of these compounds. The user of RSK Manual may opt to perform a Tier 3 analyses based upon the actual speciation of a compound detected at the site or additional toxicological data available for that compound.

After completing the site characterization and assessment of background environmental quality, if contamination is equal to or less than KDHE-approved background concentrations for the contaminants of concern, KDHE may determine that no further action is required. However, if contamination exceeds KDHE-approved background concentration, the decision should be made to remediate the site to KDHE-approved background concentrations or proceed to Tier 2 or Tier 3, as appropriate.

## 5.2 TIER 2

After completing site characterization, including characterization of background environmental quality, if appropriate, and determining the appropriate land use, the user must compare each contaminant's maximum concentration detected in soil and ground water to each contaminant's

respective concentration in the Tier 2 Risk-Based Summary Table in Appendix A. If any contaminant of concern is detected in excess of its appropriate Tier 2 value(s), KDHE may determine that remedial action is warranted. Alternatively, a Tier 3 analyses as described in Section 5.3. may be performed. If KDHE's Tier 2 Risk-Based Summary Table does not list risk-based cleanup values for contaminants of concern detected at the property, KDHE will perform the appropriate Tier 2 calculations. Periodically, KDHE will update the Tier 2 Risk-Based Summary Table and Appendices B and C as needed.

The Tier 2 Risk-Based Summary Table has six separate concentrations for each listed contaminant. For soils, the Tier 2 Risk-Based Summary Table provides two separate human health risk-based concentrations for residential and non-residential land use settings and two separate concentrations which are protective of ground water for residential and non-residential land use settings. Chemical-specific human health risk-based concentrations represent the concentrations at which the contaminants pose the maximum acceptable human health risk as a result of carcinogenic (c) or non-carcinogenic (n) toxicity. In addition, the soil saturation concentration(s) has been calculated and, if the concentration is less than the contaminant's toxicity concentration or soil to ground water pathway concentration, the soil saturation concentration is the default cleanup value. The soil saturation concentration represents the maximum concentration that a contaminant may be present in soil, given the referenced geophysical setting and each contaminant's physical and chemical properties and suggests the presence of free phase product, which must be remedied in all cases. This approach is recommended in *Risk Assessment Guidance for Superfund: Volume 1 - Human Health Evaluation Manual (Part B, Development of Risk-based Preliminary Remediation Goals, EPA/540/R-92/003, December 1991.*

Tier 2 Risk-Based Summary Table ground water concentrations are derived with the assumption that the aquifer is a source of potable water. Contaminants leaching from soil to ground water may be significant. Soil contamination cleanups may frequently be determined by chemical specific soil to ground water pathway concentrations to protect ground water quality. The Tier 2 Risk-Based Summary Table provides chemical-specific human health risk-based values for residential and non-residential land use settings. It should be noted that for those contaminants for which a federal Safe Drinking Water Act maximum contaminant level (MCL) has been promulgated into law, the Tier 2 ground water value for both residential and non-residential land use settings is the chemical-specific MCL. In the event ground water is to be used as a source of drinking water the ground water cleanup concentration defaults to the residential land use concentration irrespective of land use.

For a few contaminants listed in the Tier 2 Risk-Based Summary Table, alternative methods were employed to determine chemical-specific concentrations that are protective of human health, environmentally safe, or preserve the aesthetic quality of drinking water supplies. Alternative methods include the use of the most toxic speciation of metals, the use of health advisory data in the absence of chemical-specific toxicological data, drinking water odor and taste, and the consideration of potential for explosive environments, etc. For these contaminants, the cleanup concentrations are generally more stringent than strictly human health risk-based concentrations.

## **5.2.1 EXPOSURE ASSESSMENT**

The primary objectives of the exposure assessment are to identify potentially exposed receptors and the exposure pathways by which those receptors may be exposed to contaminants, and to measure or estimate the magnitude, duration, and frequency of exposure to environmental contamination for each receptor category. For the Tier 2 Risk-Based Summary Table, KDHE/BER divided receptors into two general categories, residents and non-residents, according to the appropriate land-use designation for each site. The significant differences between the two receptor classes include exposure frequency, exposure duration, and the consideration that children are potentially exposed at residential land-use settings and are more sensitive to environmental contaminants. The non-residential land-use setting is based upon industrial or commercial settings where adult workers are considered the potentially exposed receptor.

Human health risk-based contaminant concentrations for both residential and non-residential scenarios were calculated for soil and ground water. The soil exposure pathways evaluated in the human health risk-based calculations include incidental ingestion of soil, inhalation of airborne particulates (dusts), inhalation of chemicals volatilizing from the soil (volatile compounds only), and dermal contact with soil (organic compounds only). The reasoning for evaluating dermal contact for organics only is based upon chemical-specific absorption factors. For organics, the absorption factor is generally 1 to 30 percent; however, for non-organic contaminants, the absorption factor is generally less than 1 percent. Exposure pathways for ground water include ingestion, inhalation of chemicals volatilizing from the water (volatile compounds only), and dermal contact with water.

Default exposure factors were obtained primarily from *Risk Assessment Guidance for Superfund Supplemental Guidance Standard Default Exposure Factors* (OSWER Directive, 9285.6-03) dated March 25, 1991 and more recent information from EPA Office of Solid Waste and Emergency Response and EPA Office of Research and Development. Exposure factors used in the Tier 2 Risk-Based Summary Table are presented in Table 1 and Table 2 for ground water and soil, respectively.

For the residential land use scenario, child exposure parameters were used to evaluate non-carcinogenic risks in both soil and ground water, since child exposure parameters are more sensitive to this class of environmental contaminants. Adult exposure parameters were used to evaluate carcinogenic risks for residents because, as a result of the methodologies used to calculate risk, the exposure to adults is the most significant receptor category. Adult exposure parameters were used to evaluate both carcinogenic and non-carcinogenic risks for non-residents as they are the only receptors in a non-residential land-use setting.

Chemical-specific risk-based concentrations provided in the Tier 2 Risk-Based Summary Table combine current EPA toxicity values with "standard" exposure factors to estimate contaminant concentrations in environmental media (soil and water) that are protective of receptors, including sensitive groups (children or the elderly), over a lifetime. Chemical-specific human health risk-based concentrations were calculated for more than 150 potential contaminants, including metals, volatile organic compounds, semi-volatile organic compounds, pesticides, herbicides, and polychlorinated biphenyls (PCBs). These chemicals are listed in Appendix B with their respective chemical-specific parameters (including water solubility, Henry's Law constant, the water partition coefficient for inorganic constituents [Kd], diffusivity in air, and diffusivity in water).

## 5.2.2 TOXICITY ASSESSMENT

The primary objective of a toxicity assessment is to evaluate the inherent toxicity of contaminants, including each contaminant's potential carcinogenic risk and all other non-carcinogenic health risks. Toxicity assessments rely on scientific data available in literature on adverse effects in humans and non-human species to identify the critical toxicological effects.

For the purpose of developing the Tier 2 Risk-Based Summary Table, KDHE/BER used established contaminant-specific toxicity values developed and maintained by the EPA. EPA-approved toxicological data, known as reference doses (RfD) for non-carcinogens and slope factors (SF) for carcinogens, were obtained from the *Integrated Risk Information System* (IRIS) through June 2001, the *Health Effects Assessment Summary Table* (HEAST) through June 2001, EPA's National Center for Environmental Assessment (NCEA, formerly known as ECAO), or other appropriate EPA resources. The priority sequence among the referenced toxicological databases used from the most preferred to the least preferred is as follows: (1) IRIS, (2) HEAST, (3) NCEA, (4) withdrawn from IRIS or HEAST and under review, and (5) other EPA resources approved by KDHE. Contaminant toxicological data used in developing the Tier 2 Risk-Based Summary Table are provided in Appendix C.

Oral cancer slope factors ("SFo") and oral reference doses ("RfDo") were used for both oral and inhaled exposures for contaminants lacking inhalation values. Inhalation slope factors ("SFi") and inhalation reference doses ("RfDi") were used for the inhalation and exposure pathways. Route-to-route extrapolations were used when there were no toxicity values available for a given route of exposure. In these cases, oral toxicological data was used for dermal slope factors and dermal reference doses.

## 5.2.3 RISK CHARACTERIZATION

The final step in developing risk-based cleanup concentrations that are protective of human health is the risk characterization phase. This process integrates exposure and toxicity information to quantify contaminant-specific risk-based concentrations that are protective of human health. The risk characterization process considers the two categories of potential adverse human health effects, carcinogenic and non-carcinogenic health effects through two separate land uses, residential and non-residential. Not all contaminants are classified as carcinogens, or potential cancer-causing contaminants; however, all contaminants, including carcinogens, are evaluated based upon their respective most critical adverse health effect, whether it is the contaminant's carcinogenic toxicity or it's non-carcinogenic toxicity.

For non-carcinogens, toxicologists have determined that there is a threshold concentration below which there would be no adverse health effect to an exposed population. Toxicologists universally claim that exposure to any carcinogenic contaminant, or any carcinogenic situation, such as exposure to sunlight, cigarette smoke, etc., carries a risk of an adverse health effect, therefore human health risk is not characterized by the existence of a threshold concentration.

### 5.2.3.1 GROUND WATER

Tier 1 and Tier 2 evaluations assume that ground water from the impacted aquifer is potable in quantities capable of serving domestic needs. Accordingly, for those contaminants for which the federal Safe Drinking Water Act has promulgated primary maximum contaminant levels (MCLs), the Tier 1 and Tier 2 ground water cleanup concentrations are the MCLs. For all other contaminants addressed within this document, Equations 3-1 and 3-2 were used to calculate human health risk-based concentrations for ground water for both carcinogenic and non-carcinogenic contaminants. **If ground water is to be used for drinking water purposes at a non-residential site, the risk-based Tier 2 concentration defaults to the MCL or the residential land use concentration.** Exposure factors used in the equations are provided in Table 1. Contaminant chemical, physical, and toxicological data are provided in Appendices B and C.

### 5.2.3.2 SOILS

KDHE has identified three potential conditions which must be assessed collectively to determine the appropriate Tier 2 concentration for a contaminant in soil. The first condition is impact to human health via ingestion of contaminated soil, inhalation of volatile organic compounds and/or fugitive emission dusts, and dermal contact with contaminated soil. The second condition to be assessed is the contaminant concentration in soil which would be protective of ground water. The third condition is provided for in *Risk Assessment Guidance for Superfund: Volume 1 – Human Health Evaluation Manual (Part B, Development of Risk-based Preliminary Remediation Goals)*; which indicates that the soil saturation concentration for each contaminant be quantified to determine the concentration at which it could be reasonably assumed that free phase product is present. Under such a condition, KDHE would require remediation of the soils to mitigate the free phase contamination.

Equations used to calculate chemical-specific human health risk-based concentrations in soil for carcinogens and non-carcinogens are derived from referenced EPA guidance documents with the formulas presented in Equations 3-3 and 3-4, the exposure factors provided in Table 2, and contaminant chemical, physical, and toxicological data provided in Appendices B and C. For each of the two land uses, the Tier 2 Risk-Based Summary Table provides two separate soil concentration values. Under the “Soil Pathway” column, each chemical-specific concentration is based upon either the threat to human health or the soil saturation concentration, whichever is less. Each chemical-specific concentration is notated to inform the user as to which adverse health effect the Tier 2 Soil Pathway is based on. For carcinogenic risk, the notation is “c”. For non-carcinogenic risk, the notation is “n”. If the soil saturation concentration is used, the

notation is "s". The appropriate Tier 2 soil cleanup concentration will be the lesser of the calculated values for acceptable impact to human health, the soil saturation concentration, or potential threat to ground water.

The methodology used to determine soil cleanup levels incorporated the additive adverse human health effects associated with the inhalation of vapors from volatile organic chemical contaminated soil. EPA toxicity data indicate that risks posed from exposure to certain contaminants in soil via the inhalation pathway far outweigh the risks posed via ingestion; therefore, the human health risk-based concentrations have been calculated to address this pathway as well. For the purposes of this document, volatile organic chemicals (VOCs) are those chemicals having a Henry's Law constant greater than  $1 \times 10^{-5}$  atmospheres per cubic meter per mole (atm-m<sup>3</sup>/mol) and a molecular weight less than 200 grams/mole. These contaminants are evaluated for potential volatilization from soil or water to air using volatilization factors which are identified in Appendix B under the column "Volatization Factor" (VF). To calculate inhalation exposure risk, each contaminant's volatilization factor must first be calculated. For volatilization from water to air the volatilization factor is assumed to be 0.5 liters per cubic meter (L/m<sup>3</sup>) based upon studies by Andelman 1990. The soil-to-air VF is used to define the relationship between the concentration of the contaminant in soil and the flux of the volatilized contaminant to air. The VF equation (Equation 5-1) represents a dispersion model that simulates the dispersion of contaminants in the atmosphere.

The soil saturation concentration corresponds to the contaminant concentration in soil at which the absorptive limits of the soil particles, the solubility limits of the soil pore water, and saturation of soil pore air have been reached. Above this concentration, the contaminant may be present as a pure liquid phase for contaminants that are liquid at ambient soil temperatures and pure solid phase for compounds that are solid at ambient soil temperatures.

A soil saturation concentration has been calculated using Equation 5-2 for all organic compounds. The soil saturation concentration represents chemical-physical limits of a soil matrix as defined by the parameters provided in Equation 5-2. Since these values represent the concentration at which soil pore air is saturated with a chemical, volatile emissions reach their maximum at the soil saturation value. If the chemical-specific soil saturation concentration is less than its corresponding human health risk-based concentration, the soil saturation concentration is used as the default soil concentration Tier 2 cleanup level.

### **5.2.3.3 SOIL TO GROUND WATER PROTECTION**

The methodology for calculating soil concentrations protective to prevent the migration of soil contaminants to ground water was derived from the document titled, "*Soil Screening Guidance: Technical Background Document*", OSWER 9355.4-17A, EPA/540/R-95/128 May 1996. KDHE utilized the EPA methodology for two basic reasons. The "*Soil Screening Guidance*" document is EPA supported and extensively peer-reviewed, and the methodology presented therein is relatively simple.

Migration of a contaminant from soil to ground water can be envisioned as a two-stage process: (1) release of the contaminant in soil leachate and (2) transport of the contaminant soil leachate through the underlying soil to the aquifer and, potentially, to a receptor well. For the purposes of

this document, KDHE's Tier 2 Risk-Based Summary Table assumes the receptor well to be at the source area; therefore, fate and transport modeling is not an element of the Tier 2 Risk-Based Summary Table. KDHE has adopted EPA's screening dilution factor of 20 for calculating chemical-specific soil-to-ground water pathway concentrations.

Equation 5-3 is the soil-water partition equation used to calculate the concentration of a contaminant in soil above which a threat of the contaminant entering the ground water is a concern. Tier 2 soil-to-ground water pathway concentrations are back-calculated from acceptable ground water concentrations (MCLs or human health risk-based concentrations determined using equations 3-1 and 3-2. The acceptable ground water concentration is multiplied by the dilution factor of 20 to obtain a target leachate concentration.

Although simplified, the methodology described in this section is theoretically and operationally consistent with investigation and modeling efforts that are conducted to develop soil cleanup goals and cleanup levels for protection of ground water at Superfund sites. Simplifying assumptions for the migration to ground water pathway include:

- The source is infinite (i.e., steady-state concentrations will be maintained in ground water over the exposure period);
- Contaminants are uniformly distributed throughout the zone of contamination;
- Soil contamination extends from the surface to the ground water table (i.e., adsorption sites are filled in the unsaturated zone beneath the area of contamination);
- There is no chemical or biological degradation in the unsaturated zone;
- Equilibrium soil/water partitioning is instantaneous and linear in the contaminated soil;
- The receptor well is at the source area (i.e., there is no dilution from recharge down-gradient of the property and the well is screened within the plume);
- The aquifer is unconsolidated and unconfined (surficial);
- Aquifer properties are homogenous and isotropic;
- There is no attenuation (i.e., adsorption or degradation) of contaminants in the aquifer; and,
- The contaminant does not exist as free product in the soil at the property.

### **5.3 TIER 3**

Tier 3 offers the user the opportunity to determine site-specific risk-based contaminant concentrations that are protective of human health and the environment. Tier 3 involves a substantial increase in effort relative to Tier 1 and Tier 2, including the collection of additional site-specific geophysical data, such as vertical profiling fraction organic carbon, bulk density, aquifer characterization, and/or performing more sophisticated contaminant fate and transport

models. If the user opts to perform a Tier 3 evaluation, it must be done with KDHE/BER oversight, including the submittal of appropriate work plans to perform any necessary additional work. KDHE will not authorize the performance of a Tier 3 analysis for contaminants of concern that are regulated by federal, state or local laws, such as federal Safe Drinking Water Act which mandates MCLs for drinking water aquifers.

Performing a Tier 3 analysis will require the collection of significantly more information than that required by either Tier 1 or Tier 2. Tier 3 risk-based concentrations (RBCs) will be based on KDHE-approved predicted and validated contaminant fate and transport estimates of the contaminants of concern potential to migrate away from source areas. Tier 3 analysis will allow monitoring points of compliance to be installed away from the source area in order to verify the ongoing effectiveness of facilitated natural attenuation and biodegradation; however, such monitoring points of compliance cannot extend beyond the property boundaries without department approval. A Tier 3 sampling and analysis plan may be required beyond that required by either the Tier 1 or Tier 2 analysis. Default assumption parameters that were employed by KDHE to calculate human health risk-based cleanup goals are included in Equations 5-1 and 5-2, and Table 3. Parameters for which site-specific data may be substituted to perform a Tier 3 analysis are denoted with an asterisk. The following is a list of additional data, which may be necessary to complete a Tier 3 analysis:

- Additional geological, geophysical or hydrological data, including items such as unsaturated zone physical and geological properties (vertical distribution profiling fraction organic carbon, bulk density, total porosity, air-filled porosity, water-filled porosity, etc.), thickness of unsaturated zone, thickness of the saturated aquifer, aquifer transmissivity, hydraulic conductivity, gradient, infiltration rate, and longitudinal, lateral, and vertical dispersivities;
- Documented property ownership boundaries, current and likely future land use designations, target receptors within the area, and implementability of potential institutional controls; and,
- Any additional data necessary to perform a sophisticated contaminant fate and transport model, i.e., contaminant mass limit models, contaminant degradation rates, fraction of vegetative cover, three-dimensional source area characterization, mean wind speed, infiltration rate, etc.

A common Tier 3 analysis could be the implementation of a sophisticated contaminant fate and transport model. Any model used for a Tier 3 analysis must be approved by the department project manager and must be a public domain model. In the event a proprietary model or any other model that KDHE does not possess is used in a Tier 3 analysis, the department may request a copy of the model for review and approval. The following are examples of measures that may be undertaken as part of a Tier 3 analysis:

- The use of property-specific numerical soil or ground water modeling to predict the effect of contaminant fate and transport mechanisms, including heterogeneous geological conditions;

- Characterization of property sources and exposure pathways by using property assessment data to identify relevant sources, transport mechanisms, impacted media, and exposure pathways;
- For pesticides, standard application rates have not been documented. Accordingly, the user may perform research to determine appropriate pesticide-specific standard application rates as a Tier 3 risk analysis activity.
- Identification of all potential receptors. Actual or potential receptors should be differentiated based on current and likely future land use, and upon the ability to place institutional controls at the property to eliminate potential exposure pathways;
- An evaluation of potential remedial actions that would reduce the human health or environmental risk to acceptable levels; and,
- Determination of site-specific cleanup goals based upon site-specific data, which may result in less stringent site-specific cleanup goals.

In the event a site-specific Tier 3 analysis determines that Tier 2 cleanup goals are not protective of human health or the environment, the more stringent Tier 3 cleanup goals will be the site-specific cleanup goals for the site.

## 6.0 TOTAL PETROLEUM HYDROCARBONS

Total petroleum hydrocarbons (TPH), for the purpose of this section of the RSK Manual includes all undifferentiated hydrocarbons including carbon range compounds C<sup>5</sup> through C<sup>35</sup> containing various percentages of straight chain alkanes, branched chain alkanes, cycloalkanes, straight chain alkenes, branched chain alkenes, cycloalkenes, alkyl benzenes, naphtheno benzenes, alkyl naphthalenes and polynuclear aromatics. TPH cleanup concentrations in soil and ground water, as related to Tier 2 of this RSK Manual, shall be quantified by summing TPH using EPA SW-846 modified method 8015, also known as laboratory analytical methods OA1 for gasoline range organics (GRO) and OA2 for diesel range organics (DRO).

The use of Tier 2 values for TPH-GRO and TPH-DRO shall be used in conjunction with the values for individual constituents in order to determine site cleanup goals. These constituents include but are not limited to benzene, toluene, ethylbenzene, total xylenes (BTEX), methyl-tert-butyl-ether (MTBE), ethylene dibromide (EDB), and 1,2-dichloroethane (1,2-DCA) for TPH-GRO and chrysene, pyrene, benzo[a]pyrene, and anthracene for TPH-DRO. Please note that when a Tier 2 value is less than the method detection limit, the method detection limit becomes the Tier 2 value.

Considering that TPH detected at a site is commonly found as either GRO or DRO, KDHE has developed two separate Tier 2 risk-based concentrations based upon whether the TPH is entirely GRO or DRO. For pure GRO-type TPH, the Tier 2 cleanup concentrations are based upon the physical, chemical and toxicological properties of n-hexane. For pure DRO-type TPH, the Tier 2 cleanup concentrations are based upon the physical, chemical and toxicological properties of pyrene.

If the site has only one type of TPH (GRO or DRO), the risk-based cleanup concentrations are based upon their petroleum type as provided in Tier 2 of the RSK Manual. For sites where both types of TPH are detected, the sum of the ratios of each hydrocarbon type must be calculated as follows:

$$\frac{X}{\text{GRO Tier 2 Value}} + \frac{Y}{\text{DRO Tier 2 Value}} = N$$

Where:

X = Detected GRO Concentration

Y = Detected DRO Concentration

N = Sum

For instance, where GRO and DRO are detected at 22 mg/kg and 1,000 mg/kg respectively, the hazard index would be determined as  $N = (22/220) + (1,000/2,000)$ . Accordingly  $N = 0.6$ , which is less than 1.0, therefore this scenario would be acceptable. Any N value greater than 1.0 would be considered an excessive risk and may require corrective action as determined by the BER project manager.

Non-residential TPH standards should not be used in the following situations unless approved by the KDHE project manager:

- 1) sites where contamination is caused by a responsible party that does not own or control the property;
- 2) sites where a deed restriction can not be used to control future use of the property (i.e. assuring that the non-residential setting in the future); and
- 3) sites where contamination is located on the responsible party's property but is migrating or threatening to migrate to an adjacent property not under the ownership or control of the responsible party.

The current and future use of the property and the ownership of the property must be considered when determining the use of "Non-Residential" TPH Tier 2 levels. In most cases, the residential standards should be used as the target clean-up levels.

Independent of the TPH Tier 2 levels presented in Appendix A of this RSK Manual, all free product, including hydrocarbon saturated soil, must be addressed. KDHE has calculated soil saturation values for TPH GRO and TPH DRO of 3,300 mg/kg and 70,000 mg/kg, respectively, using the methodology described above in Section 5.2.3.2. These values are estimates, and site-specific soil saturation values can vary based upon the nature of the product released at each site. However, these soil saturation values provide a default when a site-specific soil saturation value has not been calculated.

KDHE considers any apparent product on the ground water surface to be a likely indicator of soil saturation, and therefore an indicator of the need to further evaluate the potential for free product and possible remediation at the site.

## 7.0 NITRATE AND AMMONIA

KDHE/BER has a policy, BER-RS-12 titled "Cleanup Levels for Nitrate," originally developed in 1991, which addresses soil and ground water contaminated by nitrate. Policy BER-RS-12 has been recently revised through discussions with agronomy experts at Kansas State University and those revisions are reflected in this version of the RSK Manual.

### Soil Pathway:

- In areas where no vegetation is present (i.e., contamination in a gravel roadway, parking area, etc.) the following RSK standards apply:

Upper 8 inches of soil - 85 mg/kg total nitrate plus ammonia (N);

Below 8 inches in depth - 40 mg/kg nitrate plus ammonia (N).

- In areas where vegetation is present (i.e., cultivated and cropped agricultural ground, pasture, lawn, etc.) the following RSK standards apply:

Upper 24 inches of soil - 200 mg/kg total nitrate plus ammonia (N), or the maximum application rate recommended by Kansas State University for the particular crop;

Below 24 inches in depth - 40 mg/kg nitrate plus ammonia (N).

### Ground Water Pathway:

The MCL for nitrate is 10 mg/l, measured as nitrogen; or 45 mg/l when measured as nitrate.

KDHE/BER will consider monitoring options for nitrate concentrations between 10 mg/l and 20 mg/l. This strategy for monitoring follows the agency's "Kansas Nitrate Strategy" document approved by USEPA in 1997.

KDHE/BER will also consider the following site-specific conditions when determining the appropriate response action for a site contaminated by nitrate and/or ammonia.

- 1) If it is not possible to excavate soil to reach a 40 mg/kg total nitrate plus ammonia (N) level then the responsible party must determine the vertical extent of total nitrate plus ammonia (N) contamination through vertical profiling approved by KDHE.

2) If ground water is 50 feet or less in depth then ground water monitoring wells may be requested by KDHE in the area of contamination and hydraulically down gradient to the nitrate concentration in ground water additional actions may be required:

a) If nitrate (N) in ground water is between the drinking water standard of 10mg/l and KDHE Bureau of Water's policy for public water supply wells of 20 mg/l, then the responsible party may be requested by KDHE to monitor the situation over a period of time. Note that where nitrate is detected at concentrations in excess of 10mg/l in actual private or public water supply wells, other requirements may apply as specified by the KDHE Bureau of Water "Kansas Nitrate Strategy."

b) If nitrate (N) in groundwater exceeds 20 mg/l then the responsible party may be required by KDHE to install a remedial system to hydraulically contain and/or remove the contamination.

c) If nitrate (N) in ground water is below the drinking water standard, or if the nitrate is shown to be from off-site sources, the monitoring points must be sampled in accordance with KDHE identified sites reclassification criteria to monitor ground water quality.

3) If ground water depth exceeds 50 feet, the need for installation of monitoring wells will be determined by KDHE on a case by case basis depending on ground water usage, soil type, and soil concentration of nitrate plus ammonia (N). Depending on nitrate concentrations in ground water, additional actions as described above may be required.

4) If vertical soil profiling indicates the presence of impervious bedrock (i.e. shale) isolating the nitrate/ammonia from ground water, up to 200 mg/kg nitrate plus ammonia (N) can be left in place (as determined by the KDHE project manager).

Excavation is commonly implemented as an appropriate response action to address soil contaminated with nitrate and/or ammonia. Nitrate and ammonia contaminated soil can be land applied on cultivated land at approved application rates. This approach requires the completion of the KDHE Land Application Work Plan and Agreement Form available from the KDHE project manager.

## 8.0 TABLES, FORMULAS, AND EQUATIONS

TABLE 1

### GROUND WATER EXPOSURE FACTORS

ID	Description	Residents	Non-Residents
TR	Target cancer risk	1E-06, 1E-05, 1E-04	1E-06, 1E-05, 1E-04
THI	Target hazard index	1	1
BW	Body weight (kg)		
Bwa	Adult	70	70
BWc	Child (0-6 years)	15	NA
Irw	Daily water ingestion rate (L/day)		
Irwa	Adult	2	1
Irwc	Child	1	NA
INH	Inhalation rate (m3/day)		
INHa	Adult	20	20
INHc	Child	10	NA
VFw	Volatilization Factor (L/m3)	0.5	0.5
CF	Conversion Factor (L/cm3)	0.001	0.001
SA	Skin Surface Area (cm2)		
Saa	Adult	20,000	20,000
Sac	Child	7,000	NA
Kp	Permeability coefficient (cm/hr)	Chemical-specific	Chemical-specific
ET	Exposure Time (hours/day)	1	0.5
EF	Exposure Frequency (days/year)	350	250
ED	Exposure Duration (years)		
Edca	Cancer (adult)	30	25
Ednca	Noncancer (adult)	NA	25
Edncc	Noncancer (Child)	6	NA
AT	Averaging Time		
ATca	Cancer (adult)	70	70
Atnca	Noncancer (adult)	NA	25
Atncc	Noncancer (child)	6	NA
SF	Slope Factor (carcinogens)	Chemical-specific	Chemical-specific
RfD	Reference Dose	Chemical-specific	Chemical-specific

*Risk Assessment Guidance for Superfund Volume 1 Human Health Evaluation Manual (Part A) EPA, 1991 Human Health Evaluation Manual, Supplemental Guidance "Standard Default Exposure Factors".*

*Risk Assessment Guidance for Superfund, Part B: Development of Risk-based Preliminary Remediation Goals.*

**EQUATION 3-10**

**GROUND WATER / CARCINOGENS**

$$\text{RBC (mg/L)} = \frac{\text{TR} \times \text{BW} \times \text{AT} \times 365 \text{ days / year}}{\text{EF} \times \text{ED} \left[ (\text{IR}_w \times \text{SF}_o) + (\text{VF}_w \times \text{Inh} \times \text{SF}_i) + (\text{ET} \times \text{CF} \times \text{SA} \times \text{Kp} \times \text{SF}_o) \right]}$$

**EQUATION 3-2**

**GROUND WATER / NON-CARCINOGENS**

$$\text{RBC (mg/l)} = \frac{\text{THI} \times \text{BW} \times \text{AT} \times 365 \text{ days / year}}{\text{EF} \times \text{ED} \times \left[ (\text{IR}_w \times 1/\text{RfD}_o) + (\text{VF}_w \times \text{Inh} \times 1/\text{RfD}_i) + (\text{ET} \times \text{CF} \times \text{SA} \times \text{Kp} \times 1/\text{RfD}_o) \right]}$$

**TABLE 2**

**SOIL EXPOSURE FACTORS**

<b>ID</b>	<b>Description</b>	<b>Residents</b>	<b>Non-Residents</b>
TR	Target cancer risk	1E-06, 1E-05, 1E-04	1E-06, 1E-05, 1E-04
THI	Target hazard index	1	1
BW	Body weight (kg)		
Bwa	Adult	70	70
BWc	Child (0-6 years)	15	NA
INGs	Soil ingestion rate (mg/day)		
INGsa	Adult	100	50
INGsc	Child	200	NA
INH	Soil inhalation rate (m3/day)		
INHa	Adult	20	20
INHc	Child	10	NA
VFs	Soil Volatilization Factor (m3/kg)	Chemical-specific	Chemical-specific
CF	Conversion Factor (kg/mg)	1E-06	1E-06
PEF	Particulate Emission Factor (m3/kg)	1.18E+09	1.18E+09
SA	Skin Surface Area (cm2/day)		
Saa	Adult	5000	5000
Sac	Child	1750	NA
ABS	Absorption Factor (fraction)	0.1	0.1
AF	Adherence Factor (mg/cm2)	0.2	0.2
EF	Exposure Frequency (days/year)	350	250
ED	Exposure Duration (years)		
Edca	Cancer (adult)	30	25
Ednca	Noncancer (adult)	NA	25
Edncc	Noncancer (child)	6	NA
AT	Averaging Time		
Atca	Cancer (adult)	70	70
Atnca	Noncancer (adult)	NA	25
Atncc	Noncancer (child)	6	NA
SF	Slope Factor (carcinogens)	Chemical-specific	Chemical-specific
RfD	Reference Dose	Chemical-specific	Chemical-specific

See references in Table 1

**EQUATION 3-3**

**SOIL / CARCINOGENS**

$$\text{RBC (mg/kg)} = \frac{\text{TR} \times \text{BW} \times \text{AT} \times 365 \text{ days / year}}{\text{EF} \times \text{ED} \left[ (\text{ING}_s \times \text{CF} \times \text{SF}_o) + (\text{INH} \times \text{SF}_i \times \{1/\text{VF}_s + 1/\text{PEF}\}) + (\text{SF}_o \times \text{CF} \times \text{SA} \times \text{AF} \times \text{ABS}) \right]}$$

**EQUATION 3-4**

**SOIL / NON-CARCINOGENS**

$$\text{RBC (mg/kg)} = \frac{\text{THI} \times \text{BW} \times \text{AT} \times 365 \text{ days / year}}{\text{EF} \times \text{ED} \times \left[ (\text{ING}_s \times \text{CF} \times 1/\text{RfD}_o) + (1/\text{RfD}_i \times \text{INH} \times \{1/\text{VF}_s + 1/\text{PEF}\}) + (1/\text{RfD}_o \times \text{CF} \times \text{SA} \times \text{AF} \times \text{ABS}) \right]}$$

**EQUATION 5-1 VOLATILIZATION FACTOR EQUATION AND PARAMETERS**

$$VF (m^3/kg) = \frac{Q}{C} * \frac{[(3.14)(D_A)(T)]^{1/2}}{2 \times \rho_b \times D_A} \times 10^{-4} (m^2 / cm^2)$$

$$\text{where } D_A = \frac{[(\theta_a^{10/3} D_i H' + \theta_w^{10/3} D_w) / n^2]}{\rho_b K_d + \theta_w + \theta_a H'}$$

Chemical-Specific Parameters	Default
VF = Volatilization factor (m <sup>3</sup> /kg)	--
D <sub>A</sub> = Apparent diffusivity (cm <sup>2</sup> /s)	--
Q/C = Inverse of the mean concentration at the center of square source (g/m <sup>2</sup> -s per kg/m <sup>3</sup> )	81.64
T = Exposure interval (seconds)	
Residential	9.5 E+08
Non-residential	7.9 E+08
ρ <sub>b</sub> = Dry soil bulk density (g/cm <sup>3</sup> )	1.5 *
θ <sub>a</sub> = Air filled soil porosity (Lair/Lsoil)	0.28 *
N = Total soil porosity (Lpore/Lsoil)	0.43 *
θ <sub>w</sub> = Water filled soil porosity (Lwater/Lsoil)	0.15 *
ρ <sub>s</sub> = Soil particle density (g/cm <sup>3</sup> )	2.65 *
D <sub>i</sub> = Diffusivity in air (cm <sup>2</sup> /s)	Chemical-specific
RG = Universal Gas Constant (atm-m <sup>3</sup> /mole-K)	0.000082
TEMP = Temperature (K)	293
H = Henry's Law constant (atm-m <sup>3</sup> /mol)	Chemical-specific
H' = Dimensionless Henry's Law constant	H/(RG x TEMP)
D <sub>w</sub> = Diffusivity in water (cm <sup>2</sup> /s)	Chemical-specific
K <sub>d</sub> = Soil-water partition coefficient (cm <sup>3</sup> /g) = K <sub>oc</sub> f <sub>oc</sub>	Chemical-specific
K <sub>oc</sub> = Soil organic carbon-water partition coefficient (cm <sup>3</sup> /g)	Chemical-specific
F <sub>oc</sub> = Fraction organic carbon in soil (g/g)	0.01 *

\* Asterisk notes the chemical-specific parameters that may be modified in a property-specific Tier 3 analyses.

**EQUATION 5-2 SOIL SATURATION EQUATION AND PARAMETERS**

$C_{sat} = \frac{S}{P_b} (K_d P_b + \theta_w + H' \theta_a)$	
Parameter Definition (units)	Default
Csat = Soil saturation concentration (mg/kg)	--
S = Solubility in water (mg/L-water)	chemical-specific
$\rho_b$ = Dry soil bulk density (kg/L)	1.5 *
Kd = Soil-water partition coefficient (L/kg)	Koc $\times$ foc (chemical-specific)
Koc = Soil organic carbon/water partition coefficient (L/kg)	chemical-specific
foc = Fraction organic carbon in soil (g/g)	0.01 *
$\theta_w$ = Water-filled soil porosity (Lwater/Lsoil)	0.15 *
H' = Dimensionless Henry's law constant	Chemical-specific
$\theta_a$ = Air-filled soil porosity (Lair/Lsoil)	0.28 *
n = Total soil porosity (Lpore/Lsoil)	0.43 *
$\rho_s$ = Soil particle density (kg/L)	2.65 *

\* Asterisk notes the physical and chemical-specific parameters that may be modified in a property-specific Tier 3 analysis.

**EQUATION 5-3 SOIL TO GROUND WATER MIGRATION PATHWAY EQUATION**

$$C_t = C_w \left\langle (K_d) + \frac{\theta_w + \theta_a H'}{\rho_b} \right\rangle$$

**TABLE 3 GROUND WATER PROTECTION PARAMETERS**

Parameter Definition (units)	Default
Ct = Screening level in soil (mg/kg)	--
Cw = Target soil leachate concentration (mg/l)	(non-zero MCLG, MCL, or RBC) x 20 DAF
Koc = Soil organic carbon/water partition coefficient (l/kg)	Chemical-specific (see Appendix B)
foc = Fraction organic carbon in soil (g/g)	0.01 *
Kd = Soil-water partition coefficient (L/kg)	Chemical specific for inorganic contaminants; Koc x foc for organic contaminants
θw = Water-filled soil porosity (Lwater/Lsoil)	0.30 *
θa = Air-filled soil porosity (Lair/Lsoil)	0.13 *
n = Total soil porosity (Lpore/Lsoil)	0.43 *
ρb = Dry soil bulk density (kg/L)	1.5 *
ρs = Soil particle density (kg/L)	2.65 *
RG = Universal gas constant (atm-m <sup>3</sup> /mole-K)	0.000082
TEMP = Temperature (K)	293
H' = Dimensionless Henry's Law constant	H/(RG x TEMP)
H = Henry's Law constant (atm-m <sup>3</sup> /mol)	Chemical-specific (see Appendix B)

\* Asterisk notes the physical and chemical-specific parameters that may be modified in a property-specific Tier 3 analysis.

## 9.0 REFERENCES

- American Society for Testing and Materials (ASTM), *Annual Book of ASTM Standards, Section 5, Petroleum Products, Lubricants and Fossil Fuels*, Philadelphia, 1985.
- CONCAWE, *Protection of Groundwater from Oil Pollution*, April 1979.
- Cowherd, C., G. Muleski, P. Englehart, and E. Gillete, *Rapid Assessment of Exposure to Particulate Emissions From Surface Contamination*, EPA/600/8-85/002, 1985.
- Freeze, R.A. and J.A. Cherry, *Ground Water*, Prentice-Hall Publishing Co., Englewood Cliffs, N.J., 1979.
- Hazardous Substance Data Bank*, Online search for specified chemicals, May 1998.
- Health Effects Assessment Summary Tables (HEAST), July 1997.
- Integrated Risk Information System (IRIS), July, 1997.
- Kansas Administrative Regulations K.A.R. 28-78-1 through K.A.R 28-78-12, June 1998.
- Kansas Department of Health and Environment, Bureau of Environmental Remediation Policy BER-RS-007 *Minimum Standards for Model Use*.
- Kansas Statutes Annotated 65-34,161 et.seq., *Voluntary Cleanup and Property Redevelopment Program*.
- Massachusetts Department of Environmental Protection, Bureau of Waste Site Cleanup, *Interim Final Petroleum Report: Development of Health-Based Alternative to the Total Petroleum Hydrocarbon (TPH) Parameter*, August 1994.
- Missouri Department of Natural Resources, *Draft Cleanup Levels For Missouri*, 1998.
- NIOSH, *Pocket Guide to Chemical Hazards*, June 1997.
- Payne, J.R. and C.R. Phillips, *Petroleum Spills in the Marine Environment*, Lewis Publishers, Chelsea, MI, 1985.
- Schwarzenbach et al., *Properties of Some Organic Compounds*, 1993.
- Texas Natural Resource Conservation Commission, *Updated Baseline TPH Cleanup Using the Massachusetts Surrogate Approach*, July 23, 1998.
- Texas Natural Resource Conservation Commission memo entitled, *Implementation of the Existing Risk Reduction Rule*, March 2, 1999.
- Total Petroleum Hydrocarbon Criteria Working Group Series, Volume 1, *Analyses of Petroleum Hydrocarbons in Environmental Media*, March 1998.
- Total Petroleum Hydrocarbon Criteria Working Group Series, Volume 2, *Composition of Petroleum Mixtures*, March 1998.
- Total Petroleum Hydrocarbon Criteria Working Group Series, Volume 3, *Selection of Representative TPH Fractions Based on Fate and Transport Considerations*, March 1998.
- Total Petroleum Hydrocarbon Criteria Working Group Series, Volume 4, *Development of Fraction Specific Reference Doses (RfDs) and Reference Concentrations (RfCs) for Total Petroleum Hydrocarbons*, March 1998.

- United State Army Biomedical Research & Development Lab, Technical Report 8901, *Organic Explosives & Related Compounds: Environmental & Health Considerations*, March 1989.
- United States Environmental Protection Agency, *Risk Assessment Guidance for Superfund Volume 1 Human Health Evaluation Manual (Part A)*, EPA/540/1-89/002, 1989.
- United States Environmental Protection Agency, *Risk Assessment Guidance for Superfund Volume 1 Human Health Evaluation Manual (Part B)*, EPA/540/R-92/003, 1991.
- United States Environmental Protection Agency, *Human Health Evaluation Manual, Supplemental Guidance: Standard Default Exposure Factors*, OSWER Directive 9285.6-03, 1991.
- United States Environmental Protection Agency, National Center for Environmental Assessment (NCEA).
- United States Environmental Protection Agency, *Soil Screening Guidance*, OSWER Directive 9355.4-23, EPA/540/R-96/018, 1996.
- United States Environmental Protection Agency, *Drinking Water Advisory: Consumer Acceptability Advice and Health Effects Analysis on Methyl Tertiary-Butyl Ether (MtBE)*, 1997.
- United States Environmental Protection Agency, *Superfund Chemical Data Matrix*, May 1998.
- United States Environmental Protection Agency, *Dermal Exposure Assessment Principles and Applications*, 1992.
- United States Environmental Protection Agency, Office of Water, *Drinking Water Regulations and Health Advisories*, October 1996.
- United States Environmental Protection Agency, *Exposure Factors Handbook*, EPA 600/8-89/043, July 1989.
- Weast, R.C., (ed.), *CRC Handbook of Chemistry and Physics*, 61<sup>st</sup> Edition, Cleveland, 1980-1981.

**APPENDIX A**  
**KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
Acenaphthene	83-32-9	300 s	190	0.13 n	300 s	300 s	0.49 n
Acetone	67-64-1	1700 n	1.1	0.26 n	6200 n	3.8	0.93 n
Acetophenone	98-86-2	0.50 n	0.0002	0.00002 n	1.6 n	0.0006	0.00006 n
Acrolein	107-02-8	1200 n	1.3	0.31 n	9800 n	8.6	2.0 n
Acrylamide	79-06-1	1.9 c	0.0008	0.0002 c	4.2 c	0.003	0.0006 c
Acrylonitrile	107-13-1	12 c	0.002	0.0005 c	25 c	0.004	0.001 c
Alachlor (Lasso)	15972-60-8	110 c	0.08	0.002 m	240 c	0.08	0.002 m
Aldicarb (Temik)	116-06-3	67 n	0.05	0.007 m	680 n	0.05	0.007 m
Aldrin	309-00-2	0.50 c	24	5E-05 c	1.1 c	81	0.0002 c
Anthracene	120-12-7	13 s	13 s	0.62 n	13 s	13 s	2.3 n
Antimony and compounds	7440-36-0	31 n	N/A	0.006 m	820 n	N/A	0.006 m
Arsenic	7440-38-2	11 c	5.84	0.01 m	38 c	5.84	0.01 m
Atrazine	1912-24-9	38 c	0.26	0.003 m	86 c	0.26	0.003 m
Barium	7440-39-3	5500 n	N/A	2.0 m	140000 n	N/A	2.0 m
Benzene	71-43-2	9.8 n	0.08	0.005 m	17 c	0.08	0.005 m
Benzidine	92-87-5	0.04 c	5.E-05	4E-06 c	0.08 c	0.0002	1E-05 c
Benzo(a)anthracene	56-55-3	12 c	10	0.0001 c	26 c	35	0.0004 c
Benzo(b)fluoranthene	205-99-2	12 c	19 s	9.E-05 c	19 s	19 s	0.0003 c
Benzo(k)fluoranthene	207-08-9	10 s	10 s	0.001 c	10 s	10 s	0.003 c
Benzo(a)pyrene	50-32-8	1.2 c	16 s	0.0002 m	2.6 c	16 s	0.0002 m
Benzyl Chloride	100-44-7	6.4 c	0.02	0.0008 c	10 c	0.03	0.002 c
Beryllium	7440-41-7	160 n	N/A	0.004 m	4100 n	N/A	0.004 m
Bis(2-chloroethyl)ether	111-44-4	2.3 c	0.0009	0.0001 c	3.9 c	0.002	0.0002 c
Bis(2-chloroisopropyl)ether	39638-32-9	47 c	0.25	0.003 c	82 c	0.49	0.007 c
Bis(chloromethyl)ether	542-88-1	0.004 c	4.E-06	7.E-07 c	0.006 c	7.E-06	1.E-06 c
Bis(2-ethylhexyl)phthalate	117-81-7	600 c	18000 s	0.006 m	1400 c	18000 s	0.006 m
Bromacil	314-40-9	294 s	16.2	1.56 n	294 s	105	10.12 n
Bromodichloromethane	75-27-4	14 c	1.5	0.1 m	23 c	1.5	0.1 m

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A**  
**KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
Bromoform	75-25-2	1100 c	2.1	0.1 m	2400 c	2.1	0.1 m
Bromomethane	74-83-9	4.8 n	0.02	0.004 n	15 n	0.09	0.01 n
1,3-Butadiene	106-99-0	0.14 c	0.004	0.0001 c	0.21 c	0.007	0.0003 c
n-Butylbenzene	104-51-8	140 n	8	0.021	395 s	12	0.08 n
sec-Butylbenzene	135-98-8	110 n	8	0.02 n	380 n	9	0.08 n
Butyl Benzyl Phthalate	85-68-7	1500 s	1500 s	2.1 n	1500 s	1500 s	12 n
Cadmium	7440-43-9	39 n	N/A	0.005 m	1000 n	N/A	0.005 m
Captan	133-06-2	8.8 s	8.8 s	0.24 c	8.8 s	8.8 s	0.81 c
Carbaryl (Sevin)	63-25-2	230 s	69	1.5 n	230 s	230 s	9.7 n
Carbazole	86-74-8	250 s	16	0.02 c	250 s	54	0.08 c
Carbofuran (Furadan)	1563-66-2	150 s	0.47	0.04 m	150 s	0.47	0.04 m
Carbon Disulfide	75-15-0	460 n	0.14	0.009 n	950 s	0.45	0.03 n
Carbon Tetrachloride	56-23-5	2.5 n	0.20	0.005 m	7.0 c	0.20	0.005 m
Chlordane	57-74-9	24 c	48	0.002 m	55 c	48	0.002 m
Chlorobenzene	108-90-7	78 n	4.8	0.1 m	240 n	4.8	0.1 m
Chloroform	67-66-3	3.9 c	1.2	0.1 m	6.0 c	1.2	0.1 m
Chloromethane	74-87-3	86 c	0.11	0.02 c	140 c	0.22	0.04 c
Chlorpyrifos (Lorsban/Dursban)	2921-88-2	200 n	1100	0.04 n	1700 s	1700 s	0.21 n
Chromium (total)	18540-29-9	390 n	N/A	0.1 m	4000 c	N/A	0.1 m
Chrysene	218-01-9	6.4 s	6.4 s	0.01 c	6.4 s	6.4 s	0.04 c
Copper	7440-50-8	2900 n	N/A	1.3 m	76000 n	N/A	1.3 m
Cyanazine (Bladex)	21725-46-2	10 c	0.03	0.001 c	23 c	0.11	0.003 c
Cyanide (free)	57-12-5	1600 n	N/A	0.2 m	41000 n	N/A	0.2 m
Dacthal	1861-32-1	28 s	N/A	0.11 n	28 s	2.6	0.64 n
DDD	72-54-8	35 c	190	0.0009 c	79 c	620	0.003 c
DDE	72-55-9	25 c	650	0.0007 c	56 c	2200	0.002 c
DDT	50-29-3	25 c	250	0.0005 c	56 c	660 s	0.002 c
Diazinon	333-41-5	60 n	54000 s	0.01 n	610 n	54000 s	0.08 n

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A**  
**KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway	Soil to Ground Water Protection Pathway	Ground Water Pathway	Soil Pathway	Soil to Ground Water Protection Pathway	Ground Water Pathway
		(mg/kg)	(mg/kg)	(mg/L)	(mg/kg)	(mg/kg)	(mg/L)
Dibenzo(a,h)anthracene	53-70-3	1.2 c	3.1	4.E-06 c	2.6 c	11	1.E-05 c
Dibenzofuran	132-64-9	252 n	27	0.01 n	1351 s	86.5	0.032 n
1,4-Dibromobenzene	106-37-6	670 n	3700	0.13 n	6800 n	11000 s	0.76 n
Dibromochloromethane	124-48-1	100 c	1.7	0.1 m	230 c	1.7	0.1 m
1,2-Dichlorobenzene	95-50-1	990 s	77	0.6 m	990 s	77	0.6 m
1,4-Dichlorobenzene	106-46-7	57 c	9.5	0.075 m	92 c	9.5	0.075 m
Dichlorodifluoromethane	75-71-8	98 n	7.0	0.17 n	290 n	23	0.57 n
1,1-Dichloroethane	75-34-3	660 n	3.7	0.34 n	2100 s	13	1.3 n
1,2-Dichloroethane	107-06-2	4.7 c	0.04	0.005 m	7.3 c	0.04	0.005 m
1,1-Dichloroethene	75-35-4	0.90 c	0.12	0.007 m	1.4 c	0.12	0.007 m
1,2-Dichloroethene (cis)	156-59-2	57 n	0.80	0.07 m	180 n	0.80	0.07 m
1,2-Dichloroethene (trans)	156-60-5	94 n	1.5	0.1 m	290 n	1.5	0.1 m
2,4-Dichlorophenol	120-83-2	200 n	8.8	0.04 n	2000 n	54	0.25 n
2,4-Dichlorophenoxyacetic acid (2,4-D)	94-75-7	670 n	6.6	0.07 m	3100 s	6.6	0.07 m
1,2-Dichloropropane	78-87-5	6.0 c	0.06	0.005 m	9.3 c	0.06	0.005 m
1,3-Dichloropropene	542-75-6	1.6 c	0.01	0.001 c	2.5 c	0.03	0.002 c
Dichlorvos	62-73-7	29 c	0.03	0.003 c	66 c	0.09	0.01 c
Dieldrin	60-57-1	0.53 c	0.20	5.E-05 c	1.2 c	0.66	0.0002 c
Diethyl Phthalate	84-66-2	3200 s	740	12 n	3200 s	3200 s	78 n
2,4-Dimethylphenol	105-67-9	1300 n	13	0.28 n	14000 n	81	1.8 n
2,4-Dinitrophenol	51-28-5	130 n	0.33	0.03 n	1200 s	2.1	0.20 n
2,4-Dinitrotoluene	121-14-2	13 c	0.03	0.001 c	28 c	0.09	0.004 c
2,6-Dinitrotoluene	606-20-2	13 c	0.02	0.001 c	28 c	0.07	0.004 c
Di-n-octyl Phthalate	117-84-0	1300 n	17000 s	0.002 n	14000 n	17000 s	0.008 n
1,4-Dioxane	123-91-1	770 c	0.32	0.08 c	1700 c	1.1	0.26 c
Diuron	330-54-1	133 n	3.08	0.031 n	205 s	18.99	0.191 n
Endosulfan	115-29-7	11 s	11 s	0.09 n	11 s	11 s	0.59 n
Endrin	72-20-8	20 n	4.9	0.002 m	30 s	4.9	0.002 m

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A  
KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
EPTC (Ethyl-dithiopropylcarbamate, s-)	759-94-4	1700 n	97	0.33 n	5300 s	590	2.0 n
Ethylbenzene	100-41-4	650 s	55	0.7 m	650 s	55	0.7 m
Ethylene dibromide	106-93-4	0.09 c	0.0006	5.E-05 m	0.20 c	0.0006	5.E-05 m
Fluoranthene	206-44-0	220 s	220 s	0.18 n	220 s	220 s	0.89 n
Fluorene	86-73-7	270 s	200	0.07 n	270 s	270 s	0.28 n
Fonofos (Dyfonate)	944-22-9	130 n	9.6	0.02 n	250 s	57	0.15 n
Formaldehyde	50-00-0	10000 n	13	3.0 n	60000 s	84	20 n
Furan	110-00-9	3.2 n	0.02	0.003 n	9.9 n	0.08	0.009 n
Glyphosate (Roundup)	1071-83-6	6700 n	300	0.7 m	68000 n	300	0.7 m
Heptachlor	76-44-8	1.9 c	110	0.0004 m	4.2 c	110	0.0004 m
Heptachlor Epoxide	1024-57-3	0.87 n	3.3	0.0002 m	2.1 c	3.3	0.0002 m
Hexachlorobenzene	118-74-1	5.3 c	11	0.001 m	12 c	11	0.001 m
Hexachlorobutadiene	87-68-3	13 n	18	0.002 n	140 n	100	0.009 n
Hexachloroethane	67-72-1	67 n	4.3	0.01 n	680 n	26	0.07 n
n-Hexane	110-54-3	220 s	39	0.11 n	220 s	150	0.41 n
HMX	2691-41-0	0.67 s	0.67 s	0.78 n	0.67 s	0.67 s	5.1 n
Hydrazine	302-01-2	2.8 c	100000 s	0.0003 c	6.4 c	100000 s	0.001 c
Hydrazine Sulfate	10034-93-2	2.8 c	N/A	0.0003 c	6.4 c	N/A	0.001 c
Indeno(1,2,3-cd)pyrene	193-39-5	0.76 s	0.76 s	6.E-05 c	0.76 s	0.76 s	0.0002 c
Kepone	143-50-0	0.47 c	1.5	5.E-05 c	1.1 c	5.0	0.0002 c
Lead	7439-92-1	400	N/A	0.015 m	1000	N/A	0.015 m
Lindane	58-89-9	6.6 c	0.04	0.0002 m	15 c	0.04	0.0002 m
Malathion	121-75-5	330 s	15	0.31 n	330 s	97	2.0 n
Manganese	7439-96-5	3600 n	N/A	0.05 M	95000 n	N/A	0.05 M
Mercury	7439-97-6	2 n	N/A	0.002 m	20 n	N/A	0.002 m
Methoxychlor	72-43-5	44 s	44 s	0.04 m	44 s	44 s	0.04 m
Methylene Chloride	75-09-2	150 c	0.03	0.005 m	230 c	0.03	0.005 m
Methyl Ethyl Ketone (2-Butanone)	78-93-3	6400 n	3.6	0.82 n	21000 n	12	2.8 n

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A  
KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
Methyl Isobutyl Ketone	108-10-1	1000 n	0.41	0.07 n	3600 n	1.4	0.23 n
2-Methylphenol	95-48-7	3300 n	4.6	0.74 n	6500 s	29	4.7 n
3-Methylphenol	108-39-4	3300 n	8.1	0.74 n	6500 s	29	4.7 n
4-Methylphenol	106-44-5	330 n	1.0	0.08 n	3400 n	6.5	0.47 n
Methyl Tertbutyl Ether	1634-04-4	2400 n	0.09	0.020 h	15000 n	0.09	0.020 h
Metolachlor (Dual)	51218-45-2	390 s	41	2.3 n	390 s	260	15 n
Metribuzin (Sencor)	21087-64-9	740 s	5.6	0.39 n	740 s	36	2.5 n
Naphthalene	91-20-3	100 n	39	0.10 n	320 n	140	0.35 n
Nickel	7440-02-0	1600 n	N/A	0.10 m	41000 n	N/A	0.10 m
Nitrobenzene	98-95-3	21 n	0.02	0.001 n	110 n	0.09	0.005 n
Nitrofurazone	59-87-0	5.7 c	0.002	0.0006 c	13 c	0.008	0.002 c
Nitroguanidine	55-63-0	6700 n	190	1.6 n	12000 s	1200	10 n
2-Nitropropane	79-46-9	0.91 c	0.0005	9.E-05 c	2.0 c	0.002	0.0003 c
Oxamyl	23135-22-0	1700 n	1.2	0.2 m	17000 n	1.2	0.2 m
Paraquat	1910-42-5	300 n	210	0.07 n	3100 n	1400	0.45 n
Parathion	56-38-2	380 s	98	0.08 n	380 s	380 s	0.52 n
PCBs (Polychlorinated Biphenyl)	1336-36-3	4.3 c	53	0.0005 m	9.5 c	53	0.0005 m
Pendimethalin (Prowl)	40487-42-1	37 s	37 s	0.63 n	37 s	37 s	4.1 n
Pentachlorophenol	87-86-5	71 c	20	0.001 m	160 c	20	0.001 m
Permethrin (Ambush)	52645-53-1	2.4 s	2.4 s	0.002 n	2.4 s	2.4 s	0.01 n
Phenol	108-95-2	32000 s	88	9.0 n	32000 s	560	58 n
Phenylphenol	90-43-7	4400 c	1.4	0.35 c	9800 c	4.7	1.2 c
Phosphine	7803-51-2	20 n	0.02	0.005 n	37 s	0.12	0.03 n
Profluralin	26399-36-0	100 s	100 s	0.09 n	100 s	100 s	0.61 n
Propachlor (Ramrod)	1918-16-7	550 s	4.0	0.20 n	550 s	26	1.3 n
Propazine (Miloguard)	139-40-2	5.1 s	5.1 s	0.29 n	5.1 s	5.1 s	1.9 n
n-Propylbenzene	103-65-1	140 n	11	0.02 n	400 n	44	0.08 n
Pyrene	129-00-0	140 s	140 s	0.14 n	140 s	140 s	0.72 n

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A**  
**KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
Pyridine	110-86-1	33 n	0.01	0.003 n	150 n	0.05	0.009 n
RDX	121-82-4	44 s	0.13	0.008 c	44 s	0.43	0.03 c
Selenium	7782-49-2	390 n	N/A	0.05 m	10000 n	N/A	0.05 m
Silver	7440-22-4	390 n	N/A	0.1 M	10000 n	N/A	0.1 M
Simazine (Princap)	122-34-9	9.3 s	0.13	0.004 m	9.3 s	0.13	0.004 m
Styrene	100-42-5	2400 s	16	0.1 m	2400 s	16	0.1 m
2,4,5-T as Acid	93-76-5	670 n	53	0.15 n	4800 s	340	0.94 n
2,3,7,8-TCDD (Dioxin)	1746-01-6	6.E-05 c	0.02	3.E-08 m	0.0001 c	0.02	3.E-08 m
Terbacil (Sinbar)	5902-51-2	520 s	3.3	0.20 n	520 s	22	1.3 n
Terbufos (Counter)	13071-79-9	1.7 n	0.04	0.0003 n	17 n	0.23	0.002 n
1,1,1,2-Tetrachloroethane	630-20-6	29 c	0.17	0.005 c	45 c	0.33	0.01 c
1,1,2,2-Tetrachloroethane	79-34-5	7.1 c	0.02	0.0007 c	12 c	0.03	0.001 c
Tetrachloroethene (PCE)	127-18-4	79 c	0.18	0.005 m	140 c	0.18	0.005 m
2,3,4,6-Tetrachlorophenol	58-90-2	2000 n	1200	0.27 n	20000 n	6800	1.5 n
Tetryl	479-45-8	45 s	2.2	0.16	45 s	14	1.0 n
Toluene	108-88-3	930 n	40	1 m	1000 s	40	1 m
TPH GRO		220 n	39	0.500 n	450 n	150	0.500 n
TPH DRO		2000 n	3000	0.500 n	20000 n	15000	0.720 n
Toxaphene	8001-35-2	7.7 c	150	0.003 m	17 c	150	0.003 m
2,4,5-TP (Silvex)	93-72-1	530 n	55	0.05 m	5500 n	55	0.05 m
1,2,4-Trichlorobenzene	120-82-1	600 n	25	0.07 m	4900 n	25	0.07 m
1,1,1-Trichloroethane	71-55-6	880 n	5.5	0.2 m	1800 s	5.5	0.2 m
1,1,2-Trichloroethane	79-00-5	13 c	0.07	0.005 m	20 c	0.07	0.005 m
Trichloroethene (TCE) (see note below)	79-01-6	62 c	0.20	0.005 m	98 c	0.20	0.005 m
2,4,5-Trichlorophenol	95-95-4	6700 n	1600	1.2 n	68000 n	9200	6.7 n
2,4,6-Trichlorophenol	88-06-2	770 c	45	0.05 c	1700 c	150	0.17 c
2(2,4,5-Trichlorophenoxy)propionic acid	93-72-1	530 n	130	0.12 n	5500 n	800	0.73 n
1,2,3-Trichloropropane	96-18-4	0.17 c	0.0004	2.E-05 c	0.28 c	0.0007	4.E-05 c

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**APPENDIX A  
KDHE TIER 2 RISK-BASED SUMMARY TABLE**

Chemical Name	CAS No.	RESIDENTIAL SCENARIOS			NON-RESIDENTIAL SCENARIOS		
		Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)	Soil Pathway (mg/kg)	Soil to Ground Water Protection Pathway (mg/kg)	Ground Water Pathway (mg/L)
Triflualine (Treflan)	1582-09-8	500 n	1800	0.05 c	2500 c	6000	0.18 c
1,2,4-Trimethylbenzene	95-63-6	9.7 s	0.85	0.005 n	9.7 s	2.9	0.017 n
1,3,5-Trimethylbenzene	108-67-8	2.5 n	0.24	0.005 n	69.4 n	0.83	0.017 n
2,4,6-Trinitrotoluene	118-96-7	14 s	0.05	0.008 n	14 s	3.3	0.05 n
Vanadium	7440-62-2	550 n	N/A	0.11 n	14000 n	N/A	0.71 n
Vinyl Chloride	75-01-4	0.34 c	0.02	0.002 m	0.54 c	0.02	0.002 m
Xylene (mixed)	1330-20-7	700 s	700 s	10 m	700 s	700 s	10 m
Zinc	7440-66-6	23000 n	N/A	5 M	610000 n	N/A	5 M

The RSK document should not be used for environmental audits, environmental assessments or other non-KDHE managed activities. Use of Tier 2 risk-based values established within the RSK Manual without KDHE oversight may constitute misapplication of the RSK manual and may result in risk management decisions not supported by KDHE. Please read the narrative to ensure proper use of Appendix A for KDHE managed activities.

**Notes**

n - non-carcinogenic risk, HI = 1

c - carcinogenic risk, risk =  $1 \times 10^{-5}$

s - soil saturation

m - primary maximum contaminant level (MCL)

At the time of the printing of this document, EPA was reevaluating the toxicity of TCE. Upon completion of EPA's evaluation, the soil pathway value for TCE will change accordingly.

M - secondary maximum contaminant level (MCL)

h - health advisory

N/A - insufficient data to calculate value

**APPENDIX B  
CONTAMINANT-SPECIFIC PARAMETERS**

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
Acenaphthene	4.24 a	3.92 a	3.85 a	71	1.55E-04 a	0.04 a	7.69E-06	0.150 m	3.3E+05	3.0E+05
Acenaphthylene	16.1 b	3.55 b	3.49 d	31	1.13E-04 b			0.074 m		
Acetone	1.00E+06 a	-0.24 a	-0.24 a	0.01	3.88E-05 a	0.12 a	1.14E-05	0.0012 m	1.5E+04	1.3E+04
Acetophenone	6.10E+03	1.58	1.55	0.36	1.10E-05		8.70E-06	0.0047		
Acrolein	2.13E+05 b	-0.01 b	1.33 c	0.21	1.22E-04 b	0.11 c	1.22E-05	0.00074 l		
Acrylamide	6.40E+05 b	-0.96 b	-0.94 d	0.0011	1.00E-09 b			0.00024 l		
Acrylonitrile	7.4.E+04 b	0.25 b	-0.07 c	0.01	1.03E-04 b	0.11 c	1.34E-05	0.0014 l	1.6E+05	1.5E+05
Alachlor (Lasso)	242			1.9	2.07E-08 g			0.014 m		
Aldicarb (Temik)	6030 b	1.11 b	1.09 d	0.12	1.44E-09 b			0.00084 m		
Aldrin	0.18 a	6.50 a	6.39 a	24535	1.70E-04 a	0.01 a	4.86E-06	0.0016 l		
Anthracene	0.04 a	4.55 a	4.47 a	297	6.50E-05 a	0.03 a	7.74E-06	0.23 m	1.2E+06	1.1E+06
Antimony and compounds				45				0.0010 l		
Arsenic				29				0.0010 l		
Atrazine	70 b	2.65 b	2.61 d	4.0	4.53E-03 b			0.0083 m		
Barium				41				0.0010 l		
Benzene	1750 a	2.13 a	1.77 a	0.58	5.55E-03 a	0.09 a	9.80E-06	0.021 l	3.8E+03	3.5E+03
Benzidine	500 b	1.66 b	1.63 d	0.43	3.88E-11 b			0.0013 l		
Benzo(a)anthracene	0.01 a	5.70 a	5.60 a	4012	3.35E-06 a	0.05 a	9.00E-06	0.81 l		
Benzo(b)fluoranthene	0.0015 a	6.20 a	6.09 a	12442	1.11E-04 a	0.02 a	5.56E-06	1.2 l		
Benzo(k)fluoranthene	0.0008 a	6.20 a	6.09 a	12442	8.29E-07 a	0.02 a	5.56E-06	1.1 m		
Benzo(a)pyrene	0.0016 a	6.11 a	6.01 a	10149	1.13E-06 a	0.04 a	9.00E-06	1.2 l		
Benzyl Chloride	525 b	2.30 b	1.70 c	0.50	4.15E-04 b	0.07 c	7.80E-06	0.014 l	1.5E+04	1.3E+04
Beryllium				790				0.0010 l		
Bis(2-chloroethyl)ether	1.7.E+04 a	1.21 a	1.19 a	0.15	1.80E-05 a	0.07 a	7.53E-06	0.0021 l	4.5E+04	4.1E+04
Bis(2-chloroisopropyl)ether	1310 b	2.58 b	1.79 c	0.61	1.13E-04 b	0.06 c	6.40E-06	0.010 m	3.1E+04	2.9E+04
Bis(chloromethyl)ether	3.8E+04 b	1.04 b	0.08 c	0.01	1.18E-04 c	0.09 c	9.40E-06	0.00038 m	1.0E+04	9.4E+03
Bis(2-ethylhexyl)phthalate	0.34 a	7.30 a	7.18 a	150031	1.02E-07 a	0.04 a	3.66E-06	0.033 m		
Bromacil	700 g	1.88 g	1.51 g	0.32	1.48E-10 g			0.001 m		
Bromodichloromethane	6740 a	2.10 a	1.74 a	0.55	1.60E-03 a	0.03 a	1.06E-05	0.0058 l	1.2E+04	1.1E+04
Bromoform	3100 a	2.35 a	1.94 a	0.87	5.35E-04 a	0.01 a	1.03E-05	0.0026 l		
Bromomethane	1.5.E+04 b	1.19 b	0.95 c	0.09	6.24E-03 b	0.07 c	1.20E-05	0.0035 l	2.3E+03	2.1E+03
1,3-Butadiene	735 b	1.99 b	2.08 c	1.20	7.36E-02 b	0.10 c	1.10E-05	0.023 l	1.6E+03	1.5E+03
n-Butylbenzene	14 b	4.01 b	3.45 c	28	1.30E-02 b	0.075 c	7.80E-06			
sec-Butylbenzene	17 b	3.94 b	3.34 c	22	1.90E-02 b	0.075 c	7.80E-06			
Butyl Benzyl Phthalate	2.7 a	4.84 a	4.76 a	573	1.26E-06 a	0.02 a	4.83E-06	0.073 m		

**APPENDIX B  
CONTAMINANT-SPECIFIC PARAMETERS**

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
Cadmium				75				0.0010		
Captan	3.3 b	2.45 b	2.41 d	2.6	7.19E-06 b			0.0013		
Carbaryl (Sevin)	104 b	2.36 b	2.32 d	2.1	3.46E-09 b			0.0053		
Carbazole	7.5 a	3.59 a	3.53 a	34	1.53E-08 a	0.04 a	7.03E-06	0.080		
Carbofuran (Furadan)	320 b	1.61 b	1.58 d	0.38	9.20E-05 b			0.0038		
Carbon Disulfide	1190 a	2.00 a	1.66 a	0.46	3.03E-02 a	0.10 a	1.00E-05	0.024	1.6E+03	1.4E+03
Carbon Tetrachloride	793 a	2.73 a	2.24 a	1.74	3.04E-02 a	0.08 a	8.80E-06	0.022	2.9E+03	2.7E+03
Chlordane	0.06 a	6.32 a	5.08 a	1211	4.86E-05 a	0.01 a	4.37E-06	0.052		
Chlorobenzene	472 a	2.86 a	2.34 a	2.2	3.70E-03 a	0.07 a	8.70E-06	0.041	9.2E+03	8.4E+03
Chloroform	7920 a	1.92 a	1.60 a	0.40	3.67E-03 a	0.10 a	1.00E-05	0.0089	3.7E+03	3.4E+03
Chloromethane	5330 b	0.91 b	1.54 c	0.35	8.82E-03 b	0.11 c	6.50E-06	0.0042	7.3E+03	6.7E+03
Chlorpyrifos (Lorsban/Dursban)	1.12 b	5.26 b	5.17 d	1482	2.87E-05 f			0.046		
Chromium (trivalent)				2.E+06				0.0010		
Chromium (hexavalent)				19						
Chrysene	0.0016 a	5.70 a	5.60 a	4012	9.46E-05 a	0.02 a	6.21E-06	0.81		
Copper								0.0010		
Cyanazine (Bladex)	171 b	2.20 b	2.16 d	1.5	1.00E-10 b			0.0024		
Cyanide (free)				9.9				0.0010		
Dacthal	0.50			56	2.16E-06 g			0.059		
DDD	0.09 a	6.10 a	6.00 a	9922	4.00E-06 a	0.02 a	4.76E-06	0.28		
DDE	0.12 a	6.76 a	6.65 a	44194	2.10E-05 a	0.01 a	5.87E-06	0.24		
DDT	0.03 a	6.53 a	6.42 a	26259	8.10E-06 a	0.01 a	4.95E-06	0.43		
Diazinon	40 b	3.35 b	3.29 d	20				0.013		
Dibenzo(a,h)anthracene	0.0025 a	6.69 a	6.58 a	37718	1.47E-08 a	0.02 a	5.18E-06	2.7		
Dibenzofuran	10.0 b	4.20 b	4.13 d	135	1.26E-05 b	0.06 q	1.00E-05	0.173	7.8E+05	7.1E+05
1,4-Dibromobenzene	3.45	3.75	3.05 e	11	4.00E+02 j			0.034		
Dibromochloromethane	2600 b	2.17 b	1.80 e	0.63	7.83E-04 b			0.0035		
1,2-Dichlorobenzene	156 a	3.43 a	2.79 a	6.2	1.90E-03 a	0.07 a	7.90E-06	0.061	2.2E+04	2.0E+04
1,4-Dichlorobenzene	74.0 a	3.42 a	2.79 a	6.1	2.43E-03 a	0.07 a	7.90E-06	0.062	1.9E+04	1.8E+04
Dichlorodifluoromethane	280 b	2.16 b	1.76 c	0.58	3.43E-01 b	0.08 c	1.05E-05	0.012	1.1E+03	1.0E+03
1,1-Dichloroethane	5060 a	1.79 a	1.50 a	0.31	5.62E-03 a	0.07 a	1.05E-05	0.0089	3.3E+03	3.0E+03
1,2-Dichloroethane	8520 a	1.47 a	1.24 a	0.17	9.79E-04 a	0.10 a	9.90E-06	0.0053	5.2E+03	4.8E+03
1,1-Dichloroethene	2250 a	2.13 a	1.77 a	0.58	2.61E-02 a	0.09 a	1.04E-05	0.016	1.9E+03	1.8E+03
1,2-Dichloroethene (cis)	3500 a	1.86 a	1.55 a	0.36	4.08E-03 a	0.07 a	1.13E-05	0.010	4.0E+03	3.7E+03
1,2-Dichloroethene (trans)	6300 a	2.07 a	1.72 a	0.52	9.38E-03 a	0.07 a	1.19E-05	0.014	3.2E+03	2.9E+03

**APPENDIX B  
CONTAMINANT-SPECIFIC PARAMETERS**

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
2,4-Dichlorophenol	4500 a	3.08 a	3.03 d	11	3.16E-06 a	0.03 a	8.77E-06	0.023 l		
2,4-Dichlorophenoxyacetic acid (2,4-D)	677 b	2.70 b	2.65 d	4.5	1.02E-08 b			0.0084 m		
1,2-Dichloropropane	2800 a	1.97 a	1.64 a	0.43	2.80E-03 a	0.08 a	8.73E-06	0.010 l	5.0E+03	4.6E+03
1,3-Dichloropropene	2800 a	2.00 a	1.66 a	0.46	1.77E-02 a	0.06 a	1.00E-05	0.0055 l	2.5E+03	2.3E+03
Dichlorvos	1.0.E+04 b	1.43 b	1.41 d	0.25	1.54E-03 b			0.0010 l		
Dieldrin	0.20 a	5.37 a	4.33 a	214	1.51E-05 a	0.01 a	4.74E-06	0.016 l		
Diethyl Phthalate	1080 a	2.50 a	2.46 a	2.87	4.50E-07 a	0.03 a	6.35E-06	0.0048 l		
2,4-Dimethylphenol	7870 a	2.36 a	2.32 a	2.09	2.00E-06 a	0.06 a	8.69E-06	0.015 l		
2,4-Dinitrophenol	2790 a	1.55 a	1.52 d	0.33	4.43E-07 a	0.03 a	9.06E-06	0.0018 l		
2,4-Dinitrotoluene	270 a	2.01 a	1.98 a	0.95	9.26E-08 a	0.20 a	7.06E-06	0.0038 l		
2,6-Dinitrotoluene	180 a	1.87 a	1.84 a	0.69	7.47E-07 a	0.03 a	7.26E-06	0.0025 l		
Di-n-octyl Phthalate	0.02 a	8.06 a	7.92 a	8.4.E+05	6.68E-05 a	0.02 a	3.58E-06	27 m		
1,4-Dioxane	1.00E+06 b	-0.39 b	-0.23 e	0.01	4.80E-06 b			0.00036 l		
Diuron	42 g	2.80 g	2.68 g	4.77	5.03E-10 g			0.007 m		
Endosulfan	0.51 a	4.10 a	3.33 a	21	1.12E-05 a	0.01 a	4.55E-06	0.0033 m		
Endrin	0.25 a	5.06 a	4.09 a	122	7.52E-06 a	0.01 a	4.74E-06	0.016 l		
EPTC (Ethyl-dithiopropylcarbamate, s-	370 b	3.21 b	3.16 d	14	1.07E-04 b			0.025 m		
Eradicane	344			2.0						
Ethylbenzene	169 a	3.14 a	2.56 a	3.7	7.88E-03 a	0.08 a	7.80E-06	0.074 l	8.0E+03	7.3E+03
Ethylene dibromide	4180 b	1.96 b	1.45 c	0.28	7.43E-04 b	0.07 c	8.06E-06	0.0034 l	8.4E+03	7.6E+03
Fluoranthene	0.21 a	5.12 a	5.03 a	1080	1.61E-05 a	0.03 a	6.35E-06	0.36 l		
Fluorene	2.0 a	4.21 a	4.14 a	138	6.36E-05 a	0.04 a	7.88E-06	0.36 m	7.6E+05	7.0E+05
Fonofos (Dyfonate)	13 g			19	6.48E-06 g			0.038 m		
Formaldehyde	5.50E+05 b	-0.05 b	-0.05 d	0.01	3.36E-07 b			0.0022 l		
Furan	1.0.E+04 b	1.34 b	1.08 c	0.12	5.40E-03 b	0.10 c	1.22E-05	0.0065 m	2.1E+03	2.0E+03
Glyphosate (Roundup)	1.3.E+04 g			21	1.38E-12 g			0.00018 m		
Heptachlor	0.18 a	6.26 a	6.15 a	14251	1.48E+00 b	0.01 a	5.69E-06	0.011 l	9.2E+04	
Heptachlor Epoxide	0.20 a	5.00 a	4.92 a	823	9.50E-06 a	0.01 a	4.23E-06	0.055 m		
Hexachlorobenzene	6.2 a	5.89 a	4.74 a	553	1.32E-03 a	0.05 a	5.91E-06	0.21 l		
Hexachlorobutadiene	3.2 a	4.81 a	4.73 a	535	8.15E-03 a	0.06 a	6.16E-06	0.12 l		
Hexachloroethane	50 a	4.00 a	3.25 a	18	3.89E-03 a	0.00 a	6.80E-06	0.042 l		
n-Hexane	12 b	4.00 b	2.95 c	8.9	1.43E-02 b	0.20 c	7.77E-06	0.33 m	5.6E+03	5.1E+03
HMX	5 n	0.26 n	0.54 n	0.035	2.60E-15 n			0.000046 m		
Hydrazine	1.00E+06 b	-2.07 b	-2.03 d	0.00009	4.61E-04 l			0.000041 l		
Hydrazine sulfate								0.000041 l		

**APPENDIX B  
CONTAMINANT-SPECIFIC PARAMETERS**

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
Indeno(1,2,3-cd)pyrene	0.000022	a 6.65	a 6.54	a 34453	1.60E-06	a 0.02	a 5.66E-06	1.9		
Kepone	7.6	b 5.30	b 5.21	d 1622	2.50E-08	b		0.0030		
Lead								0.0010		
Lindane	6.8	a 3.73	a 3.03	a 11	1.40E-05	a 0.01	a 7.34E-06	0.014		
Malathion	143	b 2.86	b 2.34	e 2.2	4.89E-09	b		0.0009		
Manganese								0.0010		
Mercury				52	1.14E-02	b	0.03	a 6.30E-06	0.0010	
Methoxychlor	0.05	a 5.08	a 4.99	a 986	1.58E-05	a 0.02	a 4.46E-06	0.043		
Methylene Chloride	13000	a 1.25	a 1.07	a 0.12	2.19E-03	a 0.10	a 1.17E-05	0.0045	3.2E+03	3.0E+03
Methyl Ethyl Ketone	2.23E+05	b 0.28	b 0.65	c 0.05	5.59E-05	b 0.09	c 9.80E-06	0.0011	1.7E+04	1.5E+04
Methyl Isobutyl Ketone	1.90E+04	b 1.19	b 2.11	c 1.3	1.38E-04	b 0.08	c 7.80E-06	0.0033	3.7E+04	3.3E+04
2-Methylphenol (o-Creosol)	3.10E+04	b 2.06	b 1.04	c 0.11	1.10E-06					
3-Methylphenol (m-Creosol)	2.50E+04	b 2.06	b 1.54	c 0.35	1.50E-06					
4-Methylphenol (p-Creosol)	2.15E+04	b 2.06	b 1.69	c 0.49	1.00E-06					
Methyl Tertbutyl Ether	5.00E+04	n 1.24	n 1.04	n 0.11	5.85E-04	n 0.08	o	0.0026	6.7E+03	6.1E+03
Metolachlor (Dual)	488	g		0.70	2.41E-08	g		0.0059		
Metribuzin (Sencor)	1200	b 1.70	b	0.52	8.78E-02	b		0.0015		
Naphthalene	31	a 3.36	a 3.30	a 20	4.83E-04	a 0.06	a 7.50E-06	0.069	8.4E+04	7.6E+04
Nickel				65				0.0010		
Nitrobenzene	2090	a 1.84	a 1.81	a 0.64	2.40E-05	a 0.08	a 8.60E-06	0.0070	6.3E+04	5.8E+04
Nitrofurazone								0.00017		
Nitroguanidine	1950.00	p 1.62	p 2.77	k 5.9	2.71E-07	p		0.00011		
2-Nitropropane	2.E+04	b 0.87	b 0.86	d 0.07	1.23E-04	b		0.0010		
Oxamyl	3.E+05	g		0.09	3.85E-13	g		0.00019		
Paraquat	1.E+06	h		155	1.00E-09	k		0.0053		
Parathion (ethyl)	6.5	b 3.83	b 3.77	d 58	5.65E-07	b		0.017		
PCBs (Polychlorinated Biphenyl)	0.07	b 6.04	b 5.49	a 3090	2.60E-03	b		0.0050		
Pendimethalin (Prowl)	0.28	g		134	1.21E-05	g		0.000037		
Pentachlorophenol	1950	a 5.09	a 5.00	d 1009	2.44E-08	a 0.06	a 6.10E-06	0.65		
Permethrin (Ambush)	0.01	g		393	1.87E-06	g		45		
Phenanthrene	1.15	b 4.55	b 4.47	d 297	2.33E-05	b		0.23		
Phenol	8.E+04	a 1.48	a 1.46	a 0.29	3.97E-07	a 0.08	a 9.10E-06	0.0055		
Phenylphenol								0.027		
Phosphine	370	b	b					0.0012		
Profuralin	0.10	g		1000	2.88E-04	g		0.000015		

**APPENDIX B  
CONTAMINANT-SPECIFIC PARAMETERS**

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
Propachlor (Ramros)	613 g			0.80	1.05E-07 g			0.0034 m		
Propazine (Miloguard)	3.0 g			1.6	1.28E-08 g			0.0091 m		
n-Propylbenzene	14.0	4.01	3.45	28	1.30E-02	0.075	7.80E-06			
Pyrene	0.14 a	5.11 a	5.02 a	1055	1.10E-05 a	0.03 a	7.24E-06	0.33 m		
Pyridine	1.00E+06 b	0.67 b	0.66 d	0.05	8.88E-06 b	0.09 o		0.0018 m	4.2E+04	3.9E+04
RDX	6.10E+01 n	0.87 n	1.80 n	0.63	1.20E-05 n			0.0018 m		
Selenium				5.0				0.0010 l		
Silver				8.3				0.0010 l		
Simazine (Princap)	6.2 g			1.4	9.67E-10 g			0.0040 m		
Styrene	310 a	2.94 a	2.89 a	7.8	2.75E-03 a	0.07 a	8.00E-06	0.055 l	2.0E+04	1.8E+04
2,4,5-Trichlorophenoxyacetic acid	268 b	3.31 b	3.25 d	18	8.68E-09 b			0.0088 m		
2,3,7,8-TCDD (Dioxin)	7.9E-06 b	6.53 b	6.42 d	26259	7.92E-05 b			1.4 l		
Terbacil (Sinbar)	710 g			0.63	1.88E-10 g			0.0020 m		
Terbufos (Counter)	4.5 g			6.5	2.67E-05 g			0.050 m		
1,1,1,2-Tetrachloroethane	1100 b	2.63 b	2.16 e	1.45	2.42E-03 b	0.07 c	7.90E-06	0.028 m	9.5E+03	8.7E+03
1,1,2,2-Tetrachloroethane	2970 a	2.39 a	1.97 a	0.94	3.45E-04 a	0.07 a	7.90E-06	0.0090 l	2.0E+04	1.9E+04
Tetrachloroethene (PCE)	200 a	2.67 a	2.19 a	1.56	1.84E-02 a	0.07 a	8.20E-06	0.048 l	3.7E+03	3.3E+03
2,3,4,6-Tetrachlorophenol	100 b	4.44 b	4.36 d	232	4.39E-06 b			0.11 m		
Tetryl	80 p	1.65 p	1.69 p	0.49	2.69E-11 p			0.0005 p		
Toluene	526 a	2.75 a	2.26 a	1.80	6.64E-03 a	0.09 a	8.60E-06	0.045 l	5.8E+03	5.3E+03
TPH GRO	12 b	4.00 b	2.95 c	8.90	1.43E-02 b	0.20 c	7.77E-06	0.330 m	5.6E+03	5.1E+03
TPH DRO	0.14 a	5.11 a	5.02 a	1055	1.10E-05 a	0.03 a	7.24E-06	0.330 m		
Toxaphene	0.74 a	5.50 a	5.41 a	2551	6.00E-06 a	0.01 a	4.34E-06	0.015 l		
2,4,5-TP (Silvex)	140 b	3.80 b	3.74 d	54	7.83E-11 b			0.011 l		
1,2,4-Trichlorobenzene	300 a	4.01 a	3.25 a	18	1.42E-03 a	0.03 a	8.23E-06	0.10 l	6.5E+04	5.9E+04
1,1,1-Trichloroethane	1330 a	2.48 a	2.04 a	1.10	1.72E-02 a	0.08 a	8.80E-06	0.017 l	3.1E+03	2.9E+03
1,1,2-Trichloroethane	4420 a	2.05 a	1.70 a	0.50	9.13E-04 a	0.08 a	8.80E-06	0.0084 l	9.2E+03	8.4E+03
Trichloroethene (TCE)	1100 a	2.71 a	2.22 a	1.68	1.03E-02 a	0.08 a	9.10E-06	0.016 l	4.7E+03	4.3E+03
2,4,5-Trichlorophenol	1200 a	3.90 a	3.83 d	68	4.33E-06 a	0.03 a	7.03E-06	0.052 m		
2,4,6-Trichlorophenol	800 a	3.70 a	3.64 d	43	7.79E-06 a	0.03 a	6.25E-06	0.050 l		
2(2,4,5-Trichlorophenoxy)propionic ac	140 b	3.80 b	3.74 d	54	7.83E-11 b			0.011 l		
1,2,3-Trichloropropane	1750 b	2.25 b	1.86 e	0.72	4.09E-04 b	0.07 c	7.90E-06	0.010 m	1.7E+04	1.5E+04
Trifluralin (Treflan)	8.1 b	5.32 b	5.23 d	1698	2.64E-05 b			0.11 m		
1,2,4-Trimethylbenzene	0.26	3.63	3.57	37	5.70E-03	0.075	7.10E-06			
1,3,5-Trimethylbenzene	50 c	3.42	2.91	8.2	7.70E-03	0.075	7.10E-06			

## APPENDIX B CONTAMINANT-SPECIFIC PARAMETERS

Chemical Name	Solubility (mg/L)	Log Kow	Log Koc	Kd for inorganics or Koc * foc for organics	HLC	Diffusivity in Air	Diffusivity in Water	Kp	Volatilization Factor Residential	Volatilization Factor Industrial
2,4,6-Trinitrotoluene	120 n	1.60 n	0.20 n	0.016	4.90E-09 n			0.0011 m		
Vanadium				1000				0.0010 l		
Vinyl Chloride	2760 a	1.50 a	1.27 a	0.18	2.70E-02 a	0.11 a	1.23E-06	0.0073 l	1.3E+03	1.2E+03
Xylene (mixed)	175 c	3.17 c	2.59 e	3.9	5.71E-03 c	0.08 c	8.40E-06	0.080 l	9.4E+03	8.6E+03
Zinc				62				0.0010 l		

### Footnotes

a=EPA's Soil Screening Guidance (May 1996)

b = Superfund Chemical Data Matrix <http://www.epa.gov/superfund/oerr/products/scdm/scdm.htm>

c= from EPA Region IX PRG list, 1996

d = calculated using nonionizing organic compound equation #70 from EPA's Soil Screening Guidance (May 1996)

e = calculated using equation for VOCs, chlorinated benzenes, and certain chlorinated pesticides [equation #71 from EPA's Soil Screening Guidance (May 1996)]

f = Table A-1 Water Solubility, Vapor Pressure, Henry's Law Constant, Koc, and Kow Dat: <http://www3.bae.ncsu.edu/info1/courses/bae573/models/gleams/www-docs/tabp2.txt>

g = ARS Pesticide Properties <http://www.arsusda.gov/rsml/ppdb3>

h = Table P-2 Characteristics of Pesticides sorted by Common Name

i = calculated using equation #68 from EPA's Soil Screening Guidance: Technical Background Document (May 1996):  $HLC = (VP)(M)/(S)$

j = Schwarzenbch et al., 1993 Properties of Some Organic Compounds <http://www.uc.edu/www/geology/org-cont/refer/propert.html>

k = HSDB *Hazardous Substance Data Bank*. Online search for specified chemicals. 1994

l = USEPA, *Dermal Exposure Assessment Principles & Applications*, EPA/600/8-9/011B, January 1992

m = Calculated Kp using equation from EPA's Dermal Exposure Assessment 1/92:  $\log Kp = -2.72 + 0.71 \log kow - 0.0061 MW$

n = Agency for Toxic Substances and Disease Registry

o = EPA March 93 451/R-93/001. *Air/Superfund National Technical Guidance Study Series, Model for Estimating Air Emission Rates from Superfund Remedial Action*

p = U.S. Army Biomedical Research & Development Laboratory; Technical Report 8901

q = EPA Region 9 PRG Tables, 2002

### Notes:

Chemical/Physical Parameters not found for Eradicane, Hydrazine sulfate, nitrofurazone, phenylphenol, and phosphine

Solubility: the ability or tendency of one substance to blend uniformly with another

Kow: octanol-water partition coefficient

Koc: organic carbon normalized soil-water partition coefficient for organic compounds

Kd: soil-water partition coefficient for inorganic constituents

HLC: Henry's Law constant ( $\text{atm}\cdot\text{m}^3/\text{mol}$ )

H': Henry's Law constant (unitless)

**APPENDIX C  
CONTAMINANT TOXICITY DATA**

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
Acenaphthene	NA				6.00E-02 i	6.00E-02 r	6.00E-02 r
Acenaphthylene	D						
Acetone	D				1.00E-01 i	1.00E-01 r	1.00E-01 r
Acetophenone					1.00E-01 i	5.71E-06 i	
Acrolein	C				2.00E-02 h	5.71E-06 c	2.00E-02 r
Acrylamide	B2	4.55E+00 i	4.55E+00 c	4.55E+00 r	2.00E-04 i	2.00E-04 r	2.00E-04 r
Acrylonitrile	B1	5.40E-01 i	2.38E-01 c	5.40E-01 r	1.00E-03 h	5.71E-04 c	1.00E-03 r
Alachlor (Lasso)	B2	8.05E-02 h	8.00E-02 r	8.05E-02 r	1.00E-02 i	1.00E-02 r	1.00E-02 r
Aldicarb (Temik)	D				1.00E-03 i	1.00E-03 r	1.00E-03 r
Aldrin	B2	1.70E+01 i	1.72E+01 r	1.70E+01 r	3.00E-05 i	3.00E-05 r	3.00E-05 r
Anthracene	D				3.00E-01 i	3.00E-01 r	3.00E-01 r
Antimony and compounds	D				4.00E-04 i		
Arsenic	A	1.50E+00 i	1.51E+01 c	1.50E+00 r	3.00E-04 i		
Atrazine	C	2.22E-01 h	2.22E-01 r	2.22E-01 r	3.50E-02 h	3.50E-02 r	3.50E-02 r
Barium	D				7.00E-02 i	1.43E-04 h	
Benzene	A	2.90E-02 i	2.90E-02 c	2.90E-02 r	3.00E-03 n	1.71E-03 n	3.00E-03 r
Benzidine	A	2.30E+02 i	2.30E+02 r	2.30E+02 r	3.00E-03 i	3.00E-03 r	3.00E-03 r
Benzo(a)anthracene	B2	7.30E-01 n	3.10E-01 n	7.30E-01 r			
Benzo(b)fluoranthene	B2	7.30E-01 n	3.10E-01 n	7.30E-01 r			
Benzo(k)fluoranthene	B2	7.30E-02 n	3.10E-02 n	7.30E-02 r			
Benzo(a)pyrene	B2	7.30E+00 n	3.10E+00 n	7.30E+00 r			
Benzyl Chloride	B2	1.70E-01 i	1.70E-01 r	1.70E-01 r			
Beryllium	B1		8.40E+00 c		2.00E-03 i	5.71E-06 i	2.00E-03 r
Bis(2-chloroethyl)ether	B2	1.10E+00 i	1.16E+00 c	1.10E+00 r			
Bis(2-chloroisopropyl)ether	C	7.00E-02 h	3.50E-02 c	7.00E-02 r	4.00E-02 i	4.00E-02 r	4.00E-02 r
Bis(chloromethyl)ether	A	2.20E+02 i	2.17E+02 c	2.20E+02 r			
Bis(2-ethylhexyl)phthalate	B2	1.40E-02 i	1.40E-02 r	1.40E-02 r	2.00E-02 i	2.20E-02 r	2.20E-02 r
Bromacil	C				1.00E-01 e	1.00E-01 r	1.00E-01 r
Bromodichloromethane	B2	6.20E-02 i	6.20E-02 r	6.20E-02 r	2.00E-02 i	2.00E-02 r	2.00E-02 r
Bromoform	B2	7.90E-03 i	3.85E-03 c	7.90E-03 r	2.00E-02 i	2.00E-02 r	2.00E-02 r
Bromomethane	D				1.40E-03 i	1.43E-03 c	1.40E-03 r
n-Butylbenzene					1.00E-02 n	1.00E-02 n	1.00E-02 n
sec-Butylbenzene					1.00E-02 n	1.00E-02 n	1.00E-02 n
1,3-Butadiene	B2	9.80E-01 r	9.80E-01 c	9.80E-01 r			
Butyl Benzyl Phthalate	C				2.00E-01 i	2.00E-01 r	2.00E-01 r

**APPENDIX C  
CONTAMINANT TOXICITY DATA**

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
Cadmium	B1 (inhalation)		6.30E+00 c		5.00E-04 i		
Captan	B2	3.50E-03 h	3.50E-03 r	3.50E-03 r	1.30E-01 i	1.30E-01 r	1.30E-01 r
Carbaryl (Sevin)					1.00E-01 i	1.00E-01 r	1.00E-01 r
Carbazole	B2	2.00E-02 h	2.00E-02 r	2.00E-02 r			
Carbofuran (Furadan)					5.00E-03 i	5.00E-03 r	5.00E-03 r
Carbon Disulfide	NA				1.00E-01 i	2.00E-01 i	1.00E-01 r
Carbon Tetrachloride	B2	1.30E-01 i	5.25E-02 c	1.30E-01 r	7.00E-04 i	5.71E-04 n	7.00E-04 r
Chlordane	B2	3.50E-01 i	3.50E-01 c	3.50E-01 r	5.00E-04 i	2.29E-05 r	5.00E-04 r
Chlorobenzene	D				2.00E-02 i	5.71E-03 h	2.00E-02 r
Chloroform	B2	6.10E-03 i	8.05E-02 c	6.10E-03 r	1.00E-02 i	1.00E-02 r	1.00E-02 r
Chloromethane	C	1.30E-02 h	6.30E-03 c	1.30E-02 r			
Chlorpyrifos (Lorsban/Dursban)	D				3.00E-03 i	3.00E-03 r	3.00E-03 r
Chromium (trivalent)	D				1.00E+00 i		
Chromium (hexavalent)	A		4.20E+01 c		5.00E-03 i		
Chrysene	B2	7.30E-03 n	3.10E-03 n	7.30E-03 r			
Copper	D				3.71E-02 h		
Cyanazine (Bladex)	C	8.40E-01 h	8.40E-01 r	8.40E-01 r	2.00E-03 h	2.00E-03 r	2.00E-03 r
Cyanide (free)	D				2.00E-02 i		
Dacthal					1.00E-02 i	1.00E-02 r	1.00E-02 r
DDD	B2	2.40E-01 i	2.40E-01 r	2.40E-01 r			
DDE	B2	3.40E-01 i	3.40E-01 r	3.40E-01 r			
DDT	B2	3.40E-01 i	3.40E-01 c	3.40E-01 r	5.00E-04 i	5.00E-04 r	5.00E-04 r
Diazinon					9.00E-04 h	9.00E-04 r	9.00E-04 r
Dibenzo(a,h)anthracene	B2	7.30E+00 n	3.10E+00 n	7.30E+00 r			
Dibenzofuran					4.00E-03 n	4.00E-03 n	4.00E-03 n
1,4-Dibromobenzene					1.00E-02 i	1.00E-02 r	1.00E-02 r
Dibromochloromethane	C	8.40E-02 i	8.40E-02 r	8.40E-02 r	2.00E-02 i	2.00E-02 r	2.00E-02 r
1,2-Dichlorobenzene	D				9.00E-02 i	5.71E-02 c	9.00E-02 r
1,4-Dichlorobenzene	C	2.40E-02 h	2.40E-02 r	2.40E-02 r	2.00E-01 n	2.29E-01 c	2.29E-01 r
Dichlorodifluoromethane	D				2.00E-01 i	5.71E-02 h	2.00E-01 r
1,1-Dichloroethane	C				1.00E-01 h	1.43E-01 c	1.00E-01 r
1,2-Dichloroethane	B2	9.10E-02 i	9.10E-02 c	9.10E-02 r			
1,1-Dichloroethene	C	6.00E-01 i	1.75E-01 l	6.00E-01 r	9.00E-03 i	9.00E-03 r	9.00E-03 r
1,2-Dichloroethene (cis)	D				1.00E-02 h	1.00E-02 r	1.00E-02 r
1,2-Dichloroethene (trans)	D				2.00E-02 i	2.00E-02 r	2.00E-02 r

**APPENDIX C  
CONTAMINANT TOXICITY DATA**

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
2,4-Dichlorophenol					3.00E-03 i	3.00E-03 r	3.00E-03 r
2,4-Dichlorophenoxyacetic acid (2,4-D)	D				1.00E-02 i	1.00E-02 r	1.00E-02 r
1,2-Dichloropropane	B2	6.80E-02 h	6.80E-02 r	6.80E-02 r	1.10E-03 r	1.10E-03 i	1.10E-03 r
1,3-Dichloropropene	B2	1.80E-01 h	1.30E-01 c	1.80E-01 r	3.00E-04 i	5.71E-03 c	3.00E-04 r
Dichlorvos	B2	2.90E-01 i	2.90E-01 r	2.90E-01 r	5.00E-04 i	1.43E-04 c	5.00E-04 r
Dieldrin	B2	1.60E+01 i	1.61E+01 c	1.60E+01 r	5.00E-05 i	5.00E-05 r	5.00E-05 r
Diethyl Phthalate	D				8.00E-01 i	8.00E-01 r	8.00E-01 r
2,4-Dimethylphenol					2.00E-02 i	2.00E-02 r	2.00E-02 r
2,4-Dinitrophenol					2.00E-03 i	2.00E-03 r	2.00E-03 r
2,4-Dinitrotoluene	B2	6.80E-01 i	6.80E-01 r	6.80E-01 r	2.00E-03 i	2.00E-03 r	2.00E-03 r
2,6-Dinitrotoluene	B2	6.80E-01 i	6.80E-01 r	6.80E-01 r	1.00E-03 h	1.00E-03 r	1.00E-03 r
Di-n-octyl Phthalate	NA				2.00E-02 h	2.00E-02 r	2.00E-02 r
1,4-Dioxane	B2	1.10E-02 i	1.10E-02 r	1.10E-02 r			
Diuron					2.00E-03 i2	2.00E-03 r	2.00E-03 r
Endosulfan					6.00E-03 i	6.00E-03 r	6.00E-03 r
Endrin	D				3.00E-04 i	3.00E-04 r	3.00E-04 r
EPTC (Ethyl-dithiopropylcarbamate, s-)					2.50E-02 i	2.50E-02 r	2.50E-02 r
Eradicane							
Ethylbenzene	D				1.00E-01 i	2.90E-01 c	1.00E-01 r
Ethylene dibromide	B2	8.50E+01 i	7.70E-01 c	8.50E+01 r	5.70E-05 r	5.70E-05 h	5.70E-05 r
Fluoranthene	D				4.00E-02 i	4.00E-02 r	4.00E-02 r
Fluorene	D				4.00E-02 i	4.00E-02 r	4.00E-02 r
Fonofos (Dyfonate)					2.00E-03 i	2.00E-03 r	2.00E-03 r
Formaldehyde	B1 (inhalation)		4.55E-02 c		1.50E-01 i		1.50E-01 r
Furan					1.00E-03 i	1.00E-03 r	1.00E-03 r
Glyphosate (Roundup)	D				1.00E-01 i	1.00E-01 r	1.00E-01 r
Heptachlor	B2	4.50E+00 i	4.55E+00 c	4.50E+00 r	5.00E-04 i	5.00E-04 r	5.00E-04 r
Heptachlor Epoxide	B2	9.10E+00 i	9.10E+00 c	9.10E+00 r	1.30E-05 i	1.30E-05 r	1.30E-05 r
Hexachlorobenzene	B2	1.60E+00 i	1.61E+00 c	1.60E+00 r	8.00E-04 i	8.00E-04 r	8.00E-04 r
Hexachlorobutadiene	C	7.80E-02 i	7.70E-02 c	7.80E-02 r	2.00E-04 h	2.00E-04 r	2.00E-04 r
Hexachloroethane	C	1.40E-02 i	1.40E-02 c	1.40E-02 r	1.00E-03 i	1.00E-03 r	1.00E-03 r
n-Hexane					6.00E-02 h	5.71E-02 c	6.00E-02 r
HMX					5.00E-02 i	5.00E-02 i	5.00E-02 r
Hydrazine	B2	3.00E+00 i	1.72E+01 c	3.00E+00 r			
Hydrazine sulfate	B2	3.00E+00 i	1.72E+01 c	3.00E+00 r			

**APPENDIX C  
CONTAMINANT TOXICITY DATA**

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
Indeno(1,2,3-cd)pyrene	B2	7.30E-01 n	3.10E-01 n	7.30E-01 r			
Kepone		1.80E+01 n	1.80E+01 r	1.80E+01 r			
Lead	B2						
Lindane	B2 - C	1.30E+00 h	1.30E+00 r	1.30E+00 r	3.00E-04 l	3.00E-04 r	3.00E-04 r
Malathion					2.00E-02 i	2.00E-02 r	2.00E-02 r
Manganese	D				4.67E-02 i	1.40E-05 c	4.67E-02 r
Mercury	D				3.00E-04 h	8.57E-05 c	3.00E-04 r
Methoxychlor	D				5.00E-03 i	5.00E-03 r	5.00E-03 r
Methylene Chloride	B2	7.50E-03 i	1.65E-03 c	7.50E-03 r	6.00E-02 i	8.57E-01 c	6.00E-02 r
Methyl Ethyl Ketone	D				6.00E-01 i	2.86E-01 c	6.00E-01 r
Methyl Isobutyl Ketone					8.00E-02 h	2.29E-02 c	8.00E-02 r
2-Methylphenol					5.00E-02 i	5.00E-02 i	5.00E-02 l
3-Methylphenol					5.00E-02 i	5.00E-02 i	5.00E-02 i
4-Methylphenol					5.00E-03 h	5.00E-03 h	5.00E-03 h
Methyl Tertbutyl Ether					5.00E-02 n	8.57E-01 c	5.00E-02 r
Metolachlor (Dual)	C				1.50E-01 i	1.50E-01 r	1.50E-01 r
Metribuzin (Sencor)	D				2.50E-02 i	2.50E-02 r	2.50E-02 r
Naphthalene	D				2.00E-02 i	8.57E-04 i	2.00E-02 r
Nickel	D				2.00E-02 i		
Nitrobenzene	D				5.00E-04 i	5.71E-04 c	5.00E-04 r
Nitrofurazone	B2	1.50E+00 h	9.40E+00 h	1.50E+00 r			
Nitroguanidine					1.00E-01 i	1.00E-01 r	1.00E-01 r
2-Nitropropane	B2	9.40E+00 r	9.40E+00 c	9.40E+00 r	5.71E-03 r	5.71E-03 c	5.71E-03 r
Oxamyl					2.50E-02 i	2.50E-02 r	2.50E-02 r
Paraquat	C				4.50E-03 i	4.50E-03 r	4.50E-03 r
Parathion	C				6.00E-03 h	6.00E-03 r	6.00E-03 r
PCBs (Polychlorinated Biphenyl)	B2	2.00E+00 i	2.00E+00 r	2.00E+00 r			
Pendimethalin (Prowl)					4.00E-02 i	4.00E-02 r	4.00E-02 r
Pentachlorophenol	B2	1.20E-01 i	1.20E-01 r	1.20E-01 r	3.00E-02 i	3.00E-02 r	3.00E-02 r
Permethrin (Ambush)					5.00E-02 i	5.00E-02 r	5.00E-02 r
Phenanthrene	D						
Phenol	D				6.00E-01 l	6.00E-01 r	6.00E-01 r
Phenylphenol	C	1.94E-03 h	1.90E-03 r	1.94E-03 r			
Phosphine					3.00E-04 i	8.57E-05 c	3.00E-04 r
Profluralin					6.00E-03 h	6.00E-03 r	6.00E-03 r

**APPENDIX C  
CONTAMINANT TOXICITY DATA**

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
Propachlor (Ramros)	D				1.30E-02 i	1.30E-02 r	1.30E-02 r
Propazine (Miloguard)					2.00E-02 i	2.00E-02 r	2.00E-02 r
n-Propylbenzene					1.00E-02 n	1.00E-02 n	1.00E-02 n
Pyrene	D				3.00E-02 i	3.00E-02 r	3.00E-02 r
Pyridine					1.00E-03 i	1.00E-03 r	1.00E-03 r
RDX		1.10E-01 i	1.10E-01 i	1.10E-01 r	3.00E-03 i	3.00E-03 i	3.00E-03 r
Selenium	D				5.00E-03 i		
Silver	D				5.00E-03 i		
Simazine (Princap)	C	1.20E-01 h	1.20E-01 r	1.20E-01 r	5.00E-03 i	5.00E-03 r	5.00E-03 r
Styrene	C				2.00E-01 i	2.90E-01 c	2.00E-01 r
2,4,5-T as Acid	D				1.00E-02 i	1.00E-02 r	1.00E-02 r
2,3,7,8-TCDD (Dioxin)	B2	1.50E+05 h	1.50E+05 h	1.50E+05 r			
Terbacil (Sinbar)					1.30E-02 i	1.30E-02 r	1.30E-02 r
Terbufos (Counter)					2.50E-05 h	2.50E-05 r	2.50E-05 r
1,1,1,2-Tetrachloroethane	C	2.60E-02 i	2.59E-02 c	2.60E-02 r	3.00E-02 i	3.00E-02 r	3.00E-02 r
1,1,2,2-Tetrachloroethane	C	2.00E-01 i	2.03E-01 c	2.00E-01 r			
Tetrachloroethene (PCE)	C-B2	5.20E-02 n	2.03E-03 n	5.20E-02 r	1.00E-02 i	1.14E-01 n	1.00E-02 r
2,3,4,6-Tetrachlorophenol					3.00E-02 i	3.00E-02 r	3.00E-02 r
Tetryl					1.00E-02 h	1.00E-02 r	1.00E-02 r
Toluene	D				2.00E-01 i	1.10E-01 c	2.00E-01 r
TPH GRO					6.00E-02 h	5.71E-02 c	6.00E-02 r
TPH DRO					3.00E-02 i	3.00E-02 r	3.00E-02 r
Toxaphene	B2	1.10E+00 i	1.12E+00 c	1.10E+00 r			
2,4,5-TP (Silvex)	D				8.00E-03 i	8.00E-03 r	8.00E-03 r
1,2,4-Trichlorobenzene	D				1.00E-02 i	5.70E-02 c	1.00E-02 r
1,1,1-Trichloroethane	D				3.50E-02 n	2.86E-01 n	3.50E-02 r
1,1,2-Trichloroethane	C	5.70E-02 i	5.60E-02 c	5.70E-02 r	4.00E-03 i	4.00E-03 r	4.00E-03 r
Trichloroethene (TCE) (see note below)	B2	1.10E-02 n	6.00E-03 n	1.10E-02 r			
2,4,5-Trichlorophenol					1.00E-01 i	1.00E-01 r	1.00E-01 r
2,4,6-Trichlorophenol	B2	1.10E-02 i	1.09E-02 c	1.10E-02 r			
2(2,4,5-Trichlorophenoxy)propionic acid	D				8.00E-03 i	8.00E-03 r	8.00E-03 r
1,2,3-Trichloropropane	B2	7.00E+00 h	7.00E+00 r	7.00E+00 r	6.00E-03 i	6.00E-03 r	6.00E-03 r
Triflualine (Treflan)	C	7.70E-03 i	7.70E-03 r	7.70E-03 r	7.50E-03 i	7.50E-03 r	7.50E-03 r
1,2,4-Trimethylbenzene					5.00E-02 i	1.70E-03 i	5.00E-02 r
1,3,5-Trimethylbenzene					5.00E-02 i	1.70E-03 i	5.00E-02 r

## APPENDIX C CONTAMINANT TOXICITY DATA

Chemical Name	Weight of Evidence CLASS	SFo (kg-day/mg)	SFi (kg-day/mg)	SFd (kg-day/mg)	RfDo (mg/kg-day)	RfDi (mg/kg-day)	RfDd (mg/kg-day)
2,4,6-Trinitrotoluene		3.00E-02 i	3.00E-02 i	3.00E-02 r	5.00E-04 i	5.00E-04 i	5.00E-04 r
Vanadium					7.00E-03 h		
Vinyl Chloride	A	1.90E+00 h	3.00E-01 c	1.90E+00 r			
Xylene (mixed)	D				2.00E+00 i		2.00E+00 r
Zinc	D				3.00E-01 i		
SFo = oral slope factor							
SFi = inhalation slope factor							
SFd = dermal slope factor							
RfDo = oral reference dose							
RfDi = inhalation reference dose							
RfDd = dermal reference dose							
i = Integrated Risk Information System (IRIS), EPA, 1997							
i2 = Integrated Risk Information System (IRIS), EPA, 2002							
h = Health Effects Assessment Summary Tables (HEAST), EPA, 1997							
n = National Center for Environmental Assessment (NCEA, formerly ECAO)							
r = Route to Route Extrapolation							
c = Calculated from Inhalation RfC or Unit Risk							
e = other EPA resources as approved by KDHE							
Weight of Evidence Groups: A is Human Carcinogen; B is Probable Human Carcinogen (B1-limited evidence of carcinogenicity in humans, B2 sufficient evidence of carcinogenicity in animals with inadequate or lack of evidence in humans); C is Possible Human Carcinogen; D is Not Classifiable as to Human Carcinogenicity.							
Toxicity values are not available for acenaphthylene, eradicane, or phenanthrene							
At the time of the printing of this document, EPA was reevaluating the toxicity of TCE. Upon completion of EPA's evaluation, the reference doses and slope factors of TCE will change accordingly.							